

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36 of T25-4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W. H. Byars, Contract #152 dated June 1871  
(DCSO records, Volume 9 Page 3666)

-----  
Set post cor. to secs. 25, 30, 31 and 36, from which  
An Ash 14" dia. bears N.65°E., 60 lks. dist.  
A Maple 12" dia. bears S.50°E., 45 lks. dist.  
A W.Fir 8" dia. bears S.50°W., 33 lks. dist.  
A W.Fir 16" dia. bears N.15°W., 14 lks. dist.

BLM Dependent Resurvey - Norman Price - Special Instructions  
dated April, 1940 - Survey, 1943 (DCSO recs, Vol 27 Page 11521)

-----  
Set an iron post 3 ft. long 2" dia. 28" in the ground for cor.  
of secs. 25, 30, 31 and 36, with brass cap marked:

T25S  
R4W|R3W  
S25|S30  
S36|S31

1943

from which

An I. Cedar 8" dia. bears N.13½°E., 79 lks. dist. mkd.  
T 25 S R 3 W S 30 BT.  
A Fir 16" dia. bears S.32 3/4°E., 38 lks. dist. marked  
T 25 S R 4 W S 36 B T.  
An I. Cedar 7" dia. bears S.10½°W., 46 lks. dist. mkd.  
T 25 S R 4 W S 25 B T.  
A Fir 24" dia. bears N.44½°W., 90 lks. dist. marked  
T 25 S R 4 W S 25 B T.

BLM Dependent Resurvey - Corbin; Zirpel & Roseberry - Special  
Instructions dated July 8, 1957 & July 15, 1958 - (DCSO  
records, Volume 29 Page 12262)

-----  
Found BLM 1943 brass cap, from which

A Cedar 10" dia. bears N.13½°E., 79 lks. dist. with  
scribe marks T25S R3W S30 BT visible on open blaze.  
A Cedar 13" dia. bears S.10½°E., 46 lks. dist. with a  
healed blaze.

and new bearing trees:

A Cedar 16" dia bears S.15°E. 161 lks mkd T25S R3W S31 BT  
A Cedar 18" dia bears N.7°W., 160 lks mkd T25S R4W S25 BT

FD. by Ken Hoffine, 8/2007 - M154-16

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike  
- 9/26/2007 - C.S. File 67/24-20

-----  
Both cedar trees from 1958 ren. alive & well.