

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 30; & 25 of T25-4

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Original - W. H. Byars, Contract #152 dated June 1871 (DCSO records, Volume 9 Page 3666)</p> <p>-----</p> <p>Set ¼ sec. post from which            A Laurel 12" dia. bears N.45°W., 19 lks. dist.            A Fir 10" dia. bears S.8°E., 34 lks. dist.</p>
<p>Bureau of Land Management Dependent Resurvey - Norman Price Special Instructions dated April, 1940 - Survey, 1943 (DCSO records, Volume 27 Page 11522)</p> <p>-----</p> <p>Point for orig. ¼ sec. cor., determined by reference to the record bearing and distance from the orig. SE BT. At point for corner, set an iron post 3 ft. long 1" dia. 28" in the ground, with brass cap mkd: ¼  <div style="text-align: center;">             S25   S30                             1943 from which           </div>           A Fir 18" dia. bears S.8°E., 34 lks. with blaze healed.            I re-blaze and re-mark this old BT ¼ S 30 B T.            A Fir 18" dia. bears N.81½°W., 44 lks. marked ¼ S 25 B T.            (new BT)</p>
<p>Found OK, 1958 BLM Dependent Resurvey - Corbin, Zirpel and Roseberry - (DCSO records, 12262-63)</p>
<p>FD. by Ken Hoffine, 8/2007 - M154-16</p>
<p>Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - Kody Inda - 9/11/2007 - C.S. File 67/24-17</p> <p>-----</p> <p>Found - 2½" dia., brass cap properly marked on 1" O.D. Iron pipe, firmly set, projects 4" above ground. Orig. 10" now 19" dia., D.fir stump, 6 ft tall capped w/sheet metal, partly healed single blaze w/scribing "¼" visible bears S.8°E., 22.4 ft. (agrees w/rec.) OBT 18" now 21" dia., D.Fir stump, 5 ft. tall capped w/sheet metal healed single blaze, bears N.81½°W., 29.0 ft. (agrees w/rec) 1943 BT.</p> <p>New - 12" dia., D.Fir double blazed &amp; scribed "¼ S25 CS BT" bears S.12½°W., 6.6 ft. 14" dia., D.Fir double blazed &amp; scribed "¼ S30 CS BT" bears S.30¾°E., 20.5 ft. 36" dia., I.Cedar double blazed &amp; scribed "¼ S25 CS BT" bears N.3°W., 106.7 ft.</p> <p>continued next page</p>

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 30; & S25 T25-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

11" dia., D.Fir double blazed & scribed "¼ S30 CS  
BT" bears N.65½°E., 22.0 ft.  
Note - Lies near top of cut bank of overgrown dirt road.  
Compass decl. 16¼°E.