

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & 1 of T. 25-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, Contract #52 dated Feb. 1855
(DCSO records, Volume 9 Page 3661)

Set ¼ sec. post, from which
A Maple 3" dia. bears N.68°E., 32 lks. dist.
A Redwood 3" dia. bears S.75°W., 94 lks. dist.

Bureau of Land Management Dependent Resurvey - Norman Price -
Under Special Instructions dated April 1940 - Survey, 1943
(DCSO records, Volume 27 Page 11528)

At proportional measurement, set an iron post 3 ft. long 1"
dia. 28" in the ground, with brass cap mkd: ¼
S1|S6
1944 from which
A Madrona 7" dia. bears S.44°E., 126 lks. dist. marked
on bark ¼ S 6 B T.
A Fir 5" dia. bears S.41°W., 215 lks. dist. mkd. ¼ S 1
B. T.

Douglas Co. Surveyors Office - Vernon Tracy; Mike Darby; Jack
Barnett - November 1964 - C.S. File 53/47-51

Found - 1944 U.S. brass cap & both BTs:
5" now 16" D.Fir S.41°W., 141.9 ft. shows faint scar
Did not open.
7" now 16" Laurel S.44°E., 83.2 ft. shows faint
bark scribe.
We rescribe Laurel and mark new BT:
16" Laurel S.44°E., 83.2 ft. mkd: ¼ S1 CS BT.
9" D.Fir N.36°W., 20.7 ft. mkd: ¼ S1 CS BT.
This corner lies in small opening surrounded by young fir on
West slope of hill.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J.
Flause - 1/22/98 - C.S. File 64/79-34

Found - 2½" dia., brass cap on a 1½" O.D. iron pipe,
protrudes 12" above ground. 1944
7" now 13" dia., dead Madrone, with a partially
healed single blaze, scribing visible "¼ S6
C" bears S.44°E., 85.2 ft. (Rec. S.44°E.,
83.2 ft.) 1944

(Cont. next page)

