

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION ¼ Cor. Sec. 31; & Sec. 6, T26-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #56 dated March, 1855  
(DCSO Records, Volume 9 Page 3663)

-----  
Set Qr. sec. post, from which  
A Cedar 22" dia., bears S.5°W., 150 lks. dist.  
A B.Oak 6" dia., bears N.10°E., 21 lks. dist.

-----  
Ben B. Irving, Deputy, Co. Surveyor - Wit: E. Russell  
W.C. Chapman (No reference found) Dec. 26, 1922

-----  
Identified location from original BTs. Drove 1¼" Iron pipe.  
for corner, from which:  
16" Fir bears S.5°54'E., 144 ft.  
18" Fir bears N.31°33'E., 66 ft.

-----  
GLO Dependent Resurvey by Norman D. Price, Under Special  
Instructions dated April 5, 1940 (DCSO records, Volume 27  
Page 11501)

-----  
Proportional measurement.  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground for  
¼ sec. cor., with brass cap mkd.  $\frac{1}{4} \frac{S31}{S6}$   
1943

from which  
A Fir 20" dia., bears N.26°E., 11 lks. dist., mkd. ¼  
S31 BT.  
A Fir 20" dia., bears S.61°W., 6 lks. dist., mkd. ¼  
S6 BT.

-----  
Milo Godfrey and Crew - July 31, 1962 - C.S. File 49/102-8

-----  
Found - Iron pipe with brass cap mkd: US General Land  
Office 1943  $\frac{1}{4} \frac{S31}{S6}$   
Fir stump 21", S.61°W., 4 ft. scribing still  
visible in partly closed scar "S6 BT".  
20" Fir stump N.26°E., 7.3 ft. scribing visible  
in open scar "¼ S31 BT".  
New BTs - 11" D.Fir S.11°E., 12.8 ft. mkd. "¼ S6 CS BT".  
13" D.Fir N.4°W., 17.4 ft. mkd. "¼ S31 CS BT".  
Corner is 70 ft. North of a fence line running E & W.

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION ¼ Cor. Sec. 31; & Sec. 6 of T26-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Doug. Co. Surveyors Off. - Vernon Tracy; Mike Stone; J. Layne  
Feb. 1, 1966 - C.S. File 54/7-37

-----  
Found - Brass cap set by GLO in 1943.  
Fir stumps referred to by Godfrey.  
11" D.Fir S.11°E., 12.8 ft. Alive. Face pitched  
over. We do not disturb.  
13" D.Fir N.4°W., 17.4 ft. Dead. Burned, partial  
scribe visible.

New BT - 8" D.Fir N.86°W., 51.1 ft. mkd. "¼ S31 CS BT"  
Corner is 70 ft. North of E-W fence and 20 ft. East of Creek,  
course South.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike  
- 10/8/2007 - C.S. File 67/24-30

-----  
Found - 2½" dia., brass cap properly marked on 1" O.D. iron  
pipe firmly set projects 8" above ground.  
1¼" dia., iron pipe looked for & not fd. (1922  
corner)  
Root hole with bits of burnt bark fits well with  
record (N.26°E., 7.3 ft.) 1943 BT  
Root hole depression fits well to SE (Rec. S.11°E.,  
12.8 ft.)

No sign of any other accessories noted.  
New - 3"x3" "X" chiseled on to 2 ft x 2 ft x 3 ft tall  
pointed stone, bears N.18°W., 56.6 ft.  
Piston butt maple, 11" dia., double blazed & scribed  
"¼ S6 CS BT" center of root crown bears  
S.14°W., 138.8 ft.  
3"x3" "X" chiseled onto 8 ft. x 2 ft. x 2½ ft. tall  
stone, "X" is approx 1.2 ft. below highest  
point on stone, bears N.25°E., 230.4 ft.  
Double trunk maple, westerly trunk is 24" dia.,  
burnt, hollow, mkd "X BT" on high single blaze  
center of root crown bears S.80½°E., 197.9 ft.

Nearby survey monument sign bears East 1 ft.  
Note - East-West fence to south now removed. Corner lies in  
area that appears to be periodically burned.  
Compass decl. 16¼°E.