

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3715)

-----  
Set Hemlock post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor. mkd. 1/4 S on N. face, from which

A Fir 8" dia., bears N.31°E., 12 lks. dist., mkd. 1/4 S BT.

A Fir 8" dia., bears S.19°W., 20 lks. dist., mkd. 1/4 S BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11591)

-----  
Proportional measurement. Set an iron post, 3 ft. long, 1" dia., 28" in the ground for 1/4 sec. cor. with brass cap mkd.

1/4  $\frac{S30}{S31}$

1943

from which

A Fir 22" dia., bears N.26<sup>3</sup>/<sub>4</sub>°W., 17 lks. mkd. 1/4 S 30 BT.

A Fir 20" dia., bears S.7<sup>1</sup>/<sub>4</sub>°E., 32 lks. mkd 1/4 S31 BT.

FD. by Ken Hoffine, 8/2007 - M154-16