

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3721)

Set Cedar post 3 ft. long 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on N. face, from which
A Fir 8" dia., bears N.16°E., 21 lks. dist., mkd. 1/4 S BT.
A Fir 10" dia., bears S.22°W., 37 lks. dist., mkd. 1/4 S BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Pages 11596)

Proportional measurement. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap mkd.
1/4 $\frac{S18}{S19}$
1944

from which
A Fir 42" dia., bears N.57½°E., 116 lks., mkd. 1/4 S18 BT.
A Fir 40" dia., bears S.67°W., 14 lks., mkd. 1/4 S19 BT.

Doug. County Surveyors Office - Vernon Tracy; Jack Heritage Sept. 1966 - C.S. File 54/27

Found - GLO brass cap mkd. in 1944.
40" now 42" D.Fir S.67°W., 9.2 ft., shows very good scar. Alive.
42" now 42" D.Fir N.57½°E., 76.6 ft., now stump, shows "1/4S18" scribe on unhealed blaze.
New BTs - 7" Chinquapin S.37°E., 9.2 ft. mkd. 1/4 S19 CS BT.
6" D.Fir N.58°W., 10.8 ft. mkd. 1/4 S18 CS BT.
This cor. lies on fairly steep NE slope approx. 225 ft. S.75°W., of canyon.