

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by John Littrell, under Special Instructions dated June 13, 1867 - (SEE DCS0 records in Microfiche card 2 of 9, D0041)

Set 1/4 post between secs. 7 and 18, from which
A White Fir 30" dia., bears S.43 1/4°W., 72 lks. dist.
Maple 14" dia., bears N.32°W., 16 lks. dist.

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCS0 Records, Volume 9 Page 3723-24)

To a point, 36 lks. S. of the old 1/4 sec. cor. on line between secs. 7 and 18, which is a post mkd. 1/4 S on N faces, from which
A W.Fir 30" dia., bears S.43 1/4°W., 72 lks., mkd. 1/4 S BT.
A Maple 14" dia., bears N.32°W., 16 lks., mkd. 1/4 S BT.

GL0 Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCS0 records, Volume 27 Page 11600)

The proportionate point for 1/4 sec. cor. Set an iron post 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor. with brass cap mkd.
$$\frac{1}{4} \frac{S7}{S18}$$

1944 from which
An Incense Cedar, 36" dia., bears N.65°W., 130 lks. mkd. 1/4 S 7 BT.
An Incense Cedar 14" dia., bears S.25°E., 124 lks. mkd. 1/4 S18 BT.

Doug. County Surveyors Office - Vernon Tracy; Jack Heritage July 1966 - C.S. File 54/27-23

Found - 1944 GL0 brass cap mkd. & stumps of 1944 resurvey BTs.
36" now 40" I.Cedar stump N.65°W., 85.8 ft., shows scribe up the unhealed blaze.
14" now 20" I.Cedar stump S.25°E., 81.8 ft., scribe visible on nearly healed blaze.
New BTs - 5" D.Fir N.80°W., 35.7 ft. mkd. 1/4 S7 CS BT.
14" D.Fir S.60°E., 21.0 ft. mkd. 1/4 S18 CS BT.
Corner lies on fairly steep SW slope approx. 100 ft. N.75°E. of old unused logging road, course NE-SW.

(Cont. Next Page)

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Ken Hoffine - For: Lone Rock Timber Co. - 3/2011 - M162-21

Found - 1944 GLO cap 18" above ground and leaning slightly
in a westerly direction.
18" D.Fir bears N.79½°W., 35.6 ft. (record N.80°W.,
35.7 ft) healed face and tag.
29" D.Fir bears S.58°E., 20.3 ft (record S.60°E.,
21.0 ft) healed face and tag.
Corner lies on west facing slope approx. 110 feet northeast
along section line from an old skid road.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 9/30/2024 - C.S. File 67/59-7

Found - 1944 GLO brass cap (properly mkd) proj 18" bent,
straighten, add rough stone mound.
Singed base 19" D.Fir N.83°W., 35.6 ft (rec.
N.79½°W.) Fully healed single blaze, add 3½" mag
nail, right side center.
Burned base 32" D.Fir S.59°E., 20.0 ft. (rec.
S.58°E., 20.3 ft) fully haled single blaze, add
3½" mag nail, right side center.
New - Burned, sawn 13"x1½ ft. D.Fir stump S.32½°E., 22.0
ft. 3½" mag nail, top center.
Burned, dead 10" D.Fir with line blaze for E-W-line
N.46°W., 8.6 ft. 3½" mag nail, right side center.
Note - Mon is on east-west cutting line old growth north
clear cut to south.
Area burnt 9/2020
Compass decl. 14¼°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 208598.948 E 226363.347