

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Orig. NW BT, now nearly rotted away, no scribe fd.
1944 BT to NW, now stump with pitched face.
New BT - 22" I.Cedar N.29½°W., 45.8 ft. mkd. ¼ S6 CS BT.
Corner lies on moderate SW slope, approx. 470 ft.
east of creek, course NW.

Doug. County Surveyors Office - Vernon Tracy and Crew
Feb. 5, 1968 - C.S. File 54/27-125

Found - 1944 GLO brass cap, broken off 12" below cap.
Orig. 20" now 24" Fir S.81½°W., 9.9 ft., scribe
visible on chopped out blaze. Alive.
46" now 48" Fir, alive S.23½°W., 30.4 ft., blaze
pitched over, no scribe visible, 1966 CS BT.
22" I.Cedar N.29½°W., 45.8 ft. mkd. ¼ S6 CS BT"
alive and in good condition.
For other old BTs, see report from 1966.
Set - Brass cap at cor. mkd. County Surveyors T25S R3W
Office ¼ $\frac{S6}{S7}$
1968
(Cap set in place of remaining pipe at point for ¼
cor.)
This corner lies on moderate SW slope approx. 470 ft. East of
creek, course NW. - Deposit old brass cap alongside.

Greg Lang - For: Seneca Jones Timber Co. - April 2001 -
M 138-6 & C.S. File 65/37-5D

Found - DCSO brass cap, properly mkd.
31½" Fir bears S.81½°W., 9.9 ft. Sittrell
49½" fir bears S.23°W., 28.8 ft. Price. Set spike in
the base of the tree & placed new tag.
31" Cedar bears N.28 ¾°W., 45.8 ft. Tracy. Set
spike in the base of the tree & placed new tag.
New BTs- 21½" Cedar bears N.46½°E., 28.6 ft. scribed "¼ S6"
"BT" Set spike in the base of the tree & placed
new tag.
15½" Cedar bears S.38°E., 21.2 ft. scribed "¼ S7"
"BT" Set spike in the base of the tree & placed
new tag.
Set Alum. post at corner.
Note - On SW slope.