

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. 31 & 32; 5 & 6 of T26-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #56 dated March, 1855  
(DCSO Records, Volume 9 Page 3662)

-----  
Set post cor. to secs. 31, 32, 5 and 6, from which  
A Dogwood, 5" dia., bears N.17°W., 19 lks. dist.  
A Maple 5" dia., bears N.55°E., 13 lks. dist.  
A Maple 6" dia., bears S.31°E., 37 lks. dist.  
A Red Fir 18" dia., bears S.83°W., 7 lks. dist.

-----  
GLO Dependent Resurvey by Norman D. Price, Under Special  
Instructions dated April 5, 1940 (DCSO records, Volume 27  
Pages 11501-02)

-----  
Point for original cor. of secs. 5, 6, 31 and 32, determined  
by reference to the record measurements from the original NE.,  
SW., and NW bearing trees. At point for corner,  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for  
cor. of secs. 5, 6, 31, and 32, with brass cap mkd. T25S R3W  
S31|S32  
S6|S5  
T26S  
1943

from which  
A Maple 14" dia., bears N.63½°E., 13 lks. dist., with old  
blaze decayed. (Old BT)  
A Fir 40" dia., bears S.60°W., 7 lks. dist., mkd. on bark  
T26S R3W S6 BT. (Old BT)  
A Dogwood 7" dia., bears N.9°W., 19 lks. dist., with  
blaze healed. (Old BT)  
A Fir 60" dia. bears N.12 3/4°E., 65 lks. dist. mkd. T25S  
R3W S32 BT. (New BT)  
A Fir 20" dia., bears S.58½°E., 66 lks. dist., mkd. T26S  
R3W S5 BT. (New BT)  
A Fir 22" dia., bears N.66½°W., 64 lks. dist., mkd. T25S  
R3W S31 BT. (New BT)

-----  
Doug. Co. Surveyors Office - Vernon Tracy; Mike Stone; Jack  
Heritage - February 1966 - C.S. File 54/7-42

-----  
Found - 1943 GLO brass cap & stumps of following BTs.  
(Brass cap lies at fence corner, course E-W &  
S.)

(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Orig. 40" Fir stump S.60°W., 4.6 ft. fragmentary bark scribe visible.  
60" Fir stump N.12 3/4°E. 42.9 ft., scribe & reverse visible.  
20" Fir stump S.58 1/2°E., 43.6 ft., burned. "S" scribe visible.  
22" Fir stump N.66 1/2°W., 42.2 ft., badly burned, some scribe visible.  
New BTs - 7" D.Fir N.23 1/2°E., 50.2 ft. mkd. T25S R3W S32 CS BT.  
15" D.Fir N.49°W., 130.4 ft. mkd. T25S R3W S31 CSBT.  
No trees available to SE or SW.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike  
- 10/8/2007 - C.S. File 67/24-29

-----  
Found - 2 1/2" dia., brass cap, properly marked on 2" O.D. iron pipe. BC/IP leans southerly 0.9 ft. as it is being forced to be on south side of E-W fence there is also a wire wrapped around BC/IP to tension a south fence line. Emanating from this corner . BC/IP projects 10" above ground.  
7" now 28" dia., D.Fir, faint low blaze visible bears N.19 1/4°E., 49.4' meas. 50.2 on slope (rec. N.23 1/2°E., 50.2 ft.) 1966 BT.  
60" Fir stump now indeterminate dia., x 5 ft. tall rotted D.Fir stump, partial scribing visible on rotting blaze bears N.12 3/4°E., 42.9 ft. (Agrees w/rec) 1943 BT.  
40" Fir stump now indeterminate dia., shattered 8 ft. tall rotting stump, no markings visible, bears S.60°W., 4.6 ft. (agrees w/1943 & 1966 records) OBT  
New - 32" dia., D.Fir, double blazed & scribed "T26S R3W S6 CS BT" bears S.3 1/4°W., 130.9 ft.  
12" dia., D.Fir, double blazed & scribed "T25S R3W S31 CS BT" bears N.43 1/2°W., 13.8 ft.  
Cleared to southeast - no trees available.  
Note - Lies at NE end of dirt borrow pit. Fences extend E-W & S. All distances meas. to plumb position of BC/IP  
Compass decl. 16 1/4°E.