

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3713)

-----  
Set Oak post 3" sq., 3 ft. long 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on W. face, from which

An Oak 12" dia., bears S.85°E., 10 lks. dist., mkd. 1/4 S BT.

A Laurel 20" dia., bears S.44°W., 89 lks. dist. mkd. 1/4 S BT.

-----  
GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Pages 11588-89)

-----  
Proportional measurement. Set an iron post, 3 ft. long 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4  
S31|S32  
1943

from which

A Fir 11" dia., bears S.11°E., 63 lks. dist., mkd. 1/4 S32 BT.

A Fir 18" dia., bears S.4°W., 109 lks. dist., mkd. 1/4 S31 BT.

-----  
Doug. County Surveyors Office - Bruce R. Rogers, Deputy; Wm. Stoffel; Mike Stone - July 15, 1965 - C.S. File 54/7-2

-----  
Found - 11" Fir now stump, S.11°E., 63 lks. dist., shows good scribing.

18" Fir, now burnt stump, S.4°W., 109 lks., shows scribing.

Brass cap at corner, GLO 1943.

New BTs - 12" Oak S.24°E., 25.3 ft. mkd. 1/4 S32 CS BT.

5" Oak S.61°W., 28.2 ft. mkd. 1/4 S31 CS BT.

-----  
Fd. 1943 Brass cap and 4 BTs.

BLM Dependent Resurvey, Rogers et al, Group #1386, June, 1987-Sept. 1988 - (DCSO records, Volume 48 Page 18486)