

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3713)

Set Yew post, 4 ft. long, 4" sq., 24" in ground for cor. to secs. 29, 30, 31 and 32, mkd. T25S S29 on NE., R3W S32 on SE., S31 on SW. and S30 on NW. faces, with one notch on S. and 5 notches on E. edges, from which

A Fir 24" dia., bears N.75°E., 116 lks. dist., mkd. T25S R3W S29 BT.

A Fir 48" dia., bears S.44°E., 60 lks. dist., mkd. T25S R3W S32 BT.

A Cedar 18" dia., bears S.10°W., 147 lks. dist., mkd. T25S R3W S31 BT.

A Cedar 24" dia., bears N.55°W., 23 lks. dist., mkd. T25S R3W S30 BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11589)

The original cor. of secs. 29, 30, 31 and 32, the badly disintergrated remains of a yew post on which no marks remain. At point for corner, Set an iron post, 3 ft. long 2" dea., 28 inches in the ground with remains of yew post deposited at the base for cor. of secs. 29, 30, 31 and 32, with brass cap mkd.

T25S R3W
S30|S29

S31|S32
1943

from which

A Fir 32" dia., bears N.85¼°E., 96 lks. dist., with partial scribe marks on bark blaze. (Old BT)

A Fir 64" dia., bears S.44°E., 60 lks. dist., with partial scribe marks on bark blaze. (Old BT)

An Incense Cedar 36" dia., bears S.13½°W., 147 lks. dist., with partial scribe marks on bark blaze. (Old BT)

An I. Cedar 32" dia., bears N.61½°W., 94 lks. dist., on which I uncovered partial scribe marks beneath 60 years overgrowth. (Old BT)

A Fir 30" dia., bears N.77 3/4°E., 116 lks. dist., mkd. T25S R3W S29 BT. (New BT)

A Fir 6" dia., bears S61½°E., 19 lks. dist., mkd. T25S R3W S32 BT. (New BT)

A Fir 16" dia., bears S.46°W., 74 lks. dist., mkd. T25S R3W S31 BT. (New BT)

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Doug. County Surveyors Office - Vernon Tracy; Joe Brady
Jack Heritage - June/July 1966 - C.S. File 54/27-14

Found - 1943 GL0 brass cap mkd.
30" now 42" Fir N.77 3/4°E., 76.6 ft. Alive, shows
very good scar, we do not open. (1943 BT)
Orig. 1883 BT, 32" now 42" Fir N.85¼°E., 63.4 ft.
alive, shows fragmentary bark scribe.
All other BTs are stumps or turnouts.
New BTs - 8" Maple S.6°E., 7.7 ft. mkd. T25S R3W S32 CS BT.
5" D.Fir S.74°W., 18.9 ft. mkd. S31 CS BT.
14" Laurel N.84°W., 25.1 ft. mkd. T25S R3W S29 CSBT
7" D.Fir N.11°E., 7.7 ft. mkd. T25S R3W S29 CS BT.
This corner lies on very steep south slope on E. edge of cut
off area.

Found 1943 Brass cap and nine BTs. BLM Dependent Resurvey
by Rogers, etal - Group #1386 - June 1987/Sept. 1988
(DCSO records, Volume 48 Pages 18486-87)

Russell Badgley - For: Phil Strader - 7/2021 - M178-35

Found - A 2" Iron post by Price in 1943 per DCSO records
leaning southerly and firmly set, projecting
8" above the ground with a 2½" brass cap
properly marked per the record:
From which the 1966 BTs by Tracy -
A 25" Maple bears S.6°15'E., 7.3 ft w/healed blaze.
Rec(S.6°E. 7.7')
A 17" D.Fir bears S.72°15'W., 19.0 ft w/healed
blaze. rec (S.74°W. 18.9')
A 22" Madrone bears N.85°45'W. 25.0 ft w/healed dbl
blaze. rec (N.84°W., 25.1)
A 14" D.Fir bears N.10°45'E., 7.1 ft w/healed dbl
blaze. rec(N.11°E., 7.7')
NAD 83 (2011) EPOCH 2010.00 Geodetic Coordinates:
Lat: 43°21'40.31012" N Long: 123°05'22.15239 W