

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 & 30


Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records, Volume 9 Pages 3715-16)

-----  
Set Cedar post, 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on W. face, from which  
    A Cedar 18" dia., bears S.40°E., 34 lks. dist.,  
        mkd. 1/4 S B T.  
    A Cedar 30" dia., bears N.41°W., 20 lks. dist.,  
        mkd. 1/4 S B T.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Page 11592)

-----  
The original 1/4 sec. cor., the decayed remains of a cedar stake,, 3 ft. long, 4" square on which only ax marks remain. At point for corner, set an iron post, 3 ft. long, 1" dia., 28" in the ground, with decayed remains of cedar stake deposited at the base, for 1/4 sec. cor. with brass cap mkd.



from which  
    A Red Cedar 24" dia., bears S.40°E., 22 lks. dist.,  
        with blaze healed. I reblaze and remark this old bearing tree 1/4 S 29 BT.  
    A Red Cedar 46" dia., bears N.40°W., 36 lks. dist., mkd. 1/4 S B T. I reblaze and remark this old bearing tree 1/4 S 30 B T.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; Clete Putnam - March 24, 1960 - C.S. File 49/78-2

-----  
Found - Brass cap and orig. SE BT., now badly burned stump. Orig. NW BT., now partly burned snag. No scribing on either BT. Both check for size, bearing and distance.

Note - 1944 notes of Price, reversed distances to BTs.  
New BTs - I scribe now 40" Cedar snag N.40°W., 14.5 ft. "1/4 S30 CS BT.  
          48" R.Fir bears N.61°E., 365.7 ft. scribed "1/4 S29 CS BT.

This area clearcut, no live trees near cor. Lookout on Mt. Scott bears N.82°E.

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 29 and 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Ray Tracy; Joe Brady; Jack Heritage - June/July 1966 - C.S. File 54/27-6

-----  
Found - 1943 GLO brass cap mkd. and BTs recorded in 1960.  
40" now Cedar snag, N.40°W., 14.5 ft. scribed ¼ S30  
CS BT, now stump.  
48" now 48" R.Fir snag, N.61°E., 365.7 ft. scribed  
¼ S29 CS BT.  
New BTs - 5" D.Fir S.54°W., 42.4 ft. mkd. ¼ S 30 CS BT.  
4" D.Fir S.83°E., 16.8 ft. mkd. ¼ S BT.  
Brass cap lies almost under North side of burned log. Mt.  
Scott Lookout bears N.82°E.

FD. by Ken Hoffine, 8/2007 - M154-16

Russell Badgley - For: Phil Strader - 7/2021 - M178-35

-----  
Found - A 1" iron post by Price in 1944, projecting 6" above  
the ground with a 2½" brass cap properly marked  
fd. bent-straightened and replaced:  
From which the 1966 BTs:  
A 28" D.Fir bears N.80°00'E., 17.3 FT w/healed  
blaze. rec(S.83°E., 16.8')  
A 27" D.Fir stump bears S.63°00'W., 41.0 ft. Set  
nail in center. rec (S.54°W., 42.4')  
New BTs - A 25" D.Fir bears S.25°00'E., 31.4 ft scribed "W ¼  
S29 BT" on dbl blaze.  
A 27" D.Fir bears N.0°30'E., 47.7 ft scribed "W ¼  
S29 BT" on dbl blaze.  
NAD 83 (2011) EPOCH 2010.00 Geodetic Coordinates:  
Lat: 43°22'08.95517" N Long: 123°05'24.04635" W

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 9/18/2024 - C.S. File 67/59-16

-----  
Found Ok.  
New BT tags where necessary.  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 195400.100 E 228742.343