

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3716)

Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 19, 20, 29 and 30, mkd. T25S S20 on NE., R3W S29 on SE., S30 on SW., S19 on NW faces, with 2 notches on S. and 4 notches on N. edges, from which

A Yew 8" dia., bears N.55°E., 38 lks. dist., mkd.
T25S R3W S20 BT.

A Fir 30" dia., bears S.10°E., 45 lks. dist., mkd.
T25S R3W S29 BT.

A Cedar 12" dia., bears S.61°W., 33 lks. dist., mkd.
T25S R3S S30 BT.

A Cedar 24" dia., bears N.39°W., 19 lks. dist., mkd.
T25S R3W S19 BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11592)

Proportional measurement. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 19, 20, 29 & 30, with brass cap mkd.

T25S R3W
S19|S20

S30|S29

1943

from which

A Fir 42" dia., bears N.80°E., 35 lks. dist., mkd.

T25S R3W S20 BT.

A Fir 42" dia., bears S.74½°E., 44 lks. dist., mkd.
T25S R3W S29 BT.

A Red Cedar 10" dia., bears S.73°W., 24 lks. dist., mkd. T25S R3W S30 BT.

A Fir 42" dia., bears N.85°W., 66 lks. dist., mkd.
T25S R3W S19 BT.

Doug. County Surveyors Office - Milo E. Godfrey, Deputy - Wm. Stoffel; Mike Stone - Dec. 1963 - C.S. File 49/102-10

Found - Govt. brass cap set in 1944.
Stump of 42" Fir N.80°E., 23.1 ft. scribing "SR3W"
Stump of 42" Fir S.65½°E., (Not S.74½°E.) 29.0 ft.
face badly burned, no scribing visible.

(Cont. Next Page)

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Part of 10" Cedar S.73°W., 15.8 ft. mashed into ground.
42" Fir N.85°W., 43.6 ft., uprooted, butt end 8 ft. in the air, shows scar.
New BTs - 6" Red Cedar S.83½°W., 100.6 ft. mkd. T25S R3W S30 CS BT.
24" D.Fir N.80°W., 108.7 ft. mkd. T25S R3W S19 CSBT
Rescribe- 42" Fir stump S.65½°E., 29.2 ft. mkd. S20 CS BT.
42" Fir stump N.80°E., 24.6 ft. mkd. S R 3W S29 BT.
No live trees available in NE and SE quadrants.

Found OK by DCSO, July 1966 - C.S. File 54/27-31

BLM rehabilitation of certain corners, A. Bert Skeesick, Cadastral Surveyor under Group #2000, Surveyed Sept. 2002, - (DCSO records Vol. 54 Page(s) 21124-5)

The cor. of secs. 19, 20, 29, & 30, perpetuated by Godfrey, in 1963; monumented with an iron post, 2" dia., firmly set, projecting 15" above ground, with brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Price.
A fir stump, 45" dia., bears N.80°E., 24.6 ft., with no marks visible. (Record, 23.1 ft.)
A fir stump, 52" dia., bears S.64¾°E., 29.0 ft., with scribe marks S29 CS BT visible on open blaze. (Record, S.74¼°E.) Note: Godfrey indicates this was a stump, 42 ins. diam., in 1963 and he rescribed it S20 CS BT.
A roothole bears N.88°W., 43.6 ft., with fallen trunk, 42" dia., species indeterminate, lying alongside, with a healed blaze. (Record, fir, N.85°W.)
and the remains of the bearing trees mkd. by Godfrey.
A cedar, 21" dia, bears S.83½°W., 100.6 ft. dist., with healed blaze.
A sawed fir stump, 26" dia., bears N.80°W., 108.7 ft., with fragmentary scribe marks visible on a partially healed blaze.
and new bearing trees
A fir, 13" dia., bears N.63°E., 19.1 ft., mkd. T25S R3W S20 BT.
A fir, 16" dia., bears S.41¾°E., 39.5 ft., mkd. T25S R3W S29 BT.
A fir, 10" dia., bears N.61¼°W., 32.9 ft., mkd. T25S R3W S19 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center. continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs 19, 20, 29, & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The geographic position (NAD 1983) of this cor., as determined by a differentially corrected, mapping grade direct GPS observation is as follows.
Latitude: 43°22' 36.29" N., Longitude: 123°05'22.57"W.

FD. by Ken Hoffine, 8/2007 - M154-16

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2500, Surveyed March/May 2012 - DCSO records BLM Plat 2013-1, T25-3 and Vol. 58 Page(s) 22976

The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2" dia., firmly set, projecting 16" above ground, with brass cap (properly) mkd.
from which the remains of BTs mkd. by Price
A sawed fir stump, 45" dia., bears N.80°E., 24.6 ft., with no marks visible.
A sawed fir stump. 51" dia., bears S.64¾°E., 29.0 ft., with scribe marks S29 S BT visible on an open blaze.
A roothole bears N.88°W., 43.6 ft., with fallen trunk, 40" dia.. lying alongside. with a healed blaze.
and the remains of BTs mkd. by Godfrey, in (963,
A cedar, 24" dia., bears S.83½°W., 100.6 ft., with a healed blaze.
A sawed fir stump, 26" dia., bears N.80°W., 108.7 ft., with fragmentary scribe marks visible on a partially healed blaze.
and BTs mkd. by Skeesick
A fir, (5" dia., bears N.63°E., 19.1 ft., with fragmentary scribe marks visible on a partially healed blaze.
A fir, 18" dia., bears S.41¾°E., 39.5 ft., with a healed blaze.
A fir, 11" dia., bears N.61¼°W., 32.9 ft., with a healed blaze.
and a new accessory
An iron rebar, 30" long, 5/8" dia., driven 29" in the ground for a reference monument, bears S.43°11'00"W., 35.00 ft., with aluminum cap mkd. RM T25S R3W S30 35.0 FT TO COR 2012 and an arrow pointing to the cor.
Latitude 43°22'36.31"N Longitude 123°05'22.50"W
(NAD 1983 (CORS 96))