

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3722)

-----

Set Cedar post, 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on W. face, from which  
A Cedar 20" dia., bears N.10°E., 32 lks., mkd 1/4 S BT.  
A Hemlock 24" dia., bears S.16°W., 23 lks. mkd. 1/4 S BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Pages 11597-98)

-----

Proportional measurement. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap mkd. 1/4  
S18|S17  
1944 from which  
A Fir 28" dia., bears S.17°E., 34 lks., mkd. 1/4 S17 BT.  
A Fir 24" dia., bears N.7 1/2°W., 45 lks., mkd. 1/4 S18 BT.

Doug. County Surveyors Office - Milo Godfrey, Deputy; Wm. Stoffel; Mike Stone - Nov. 1964 - C.S. File 53/47

-----

Found - 30" Fir S.17°E., 22.4 ft., scribing visible in previously opened scar.  
32" Fir N.7 1/2°W., 29.7 ft., scar healed over, but very plain.  
No brass cap at corner; obviously destroyed in logging. (GLO 1944 cap)  
Set - Brass cap at cor. mkd. County Surveyor's Office 1964  
T25S R3W 1/4 S18|S17  
Both BTs alive & in good condition, no other trees near.

Ken Hoffine - For: Lone Rock Timber Co. - 3/2011 - M162-21

-----

Found - 1964 County Surveyors Office cap 0.5 above ground set from 1944 GLO BT  
34" D. Fir stump bears S.17°E., 22.4 ft as per record healed face and tag.  
34" D. Fir bears N.7 1/2°W., 29.7 ft as per record healed face and tag.  
Corner lies on NW facing slope approx. 150 ft from ridge top.