

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec Cor for 7, 8, 17 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3722)

-----  
Set Yew post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 7, 8, 17 and 18, mkd. T25S S8 on NE., R3W S17 on SE., S18 on SW., and S7 on NW. faces, with 4 notches on S. and 5 notches on E. edges, from which  
A Laurel 4" dia., bears N.13°E., 26 lks. dist., mkd. T25S R3W S8 BT.  
A Fir 6 dia., bears S.35°E., 30 lks. dist., mkd. T25S R3W S17 BT.  
A Fir 24" dia., bears S.77°W., 21 lks. dist., mkd. T25S R3W S18 BT.  
A Laurel 10" dia., bears N.18°W., 49 lks. dist., mkd. T25S R3W S7 BT.

GL0 Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11598)

-----  
Proportional measurement. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd.  
T25S R3W  
S7|S8  
-----  
S18|S17  
1944  
from which  
An I.Cedar 36" dia., bears N.78°E., 214 lks. dist., mkd. T25S R3W S8 BT.  
A Fir 30" dia., bears S.42°E., 87 lks. dist., mkd. T25S R3W S17 BT.  
A Madrona 5" dia., bears S.41°W., 3 lks. dist., mkd. on bark T25S R3W S18 BT.  
A Fir 24" dia., bears N.61°W., 27 lks. dist., mkd. T25S R3W S7 BT.  
This sec. cor. is located on a spur, slopes SE.

Doug. County Surveyors Office - Vernon Tracy; Jack Heritage; Joe Brady - August 1966 - C.S. File 54/27-37

-----  
Found - GL0 brass cap, 1944.  
36" now 50" I.Cedar N.78°E., 141.2 ft., shows scribe on unhealed blaze. N and NE side of tree badly burned. Tree alive.

(Cont. Next Page)

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec Cor for 7, 8, 17 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

30" now 42" Fir S.42°E., 57.4 ft. Alive, blaze pitched over.  
5" Madrone, now stub only, 6 ft. high S.41°W., 2.0'.  
24" now 28" Fir turned out, face down, N.61°W., 17.8 ft., blaze visible  
New BTs - 10" Laurel N.56°W., 26.6 ft. mkd. T25S R3W S7 CS BT.  
4" D.Fir S.71½°W., 29.6 ft. mkd. S18 CS BT.  
20" D.Fir N.78°E., 12.7 ft. mkd. T25S R3W S8 CS BT.  
Corner lies on top of rocky spur, course S.40°E.

Fd. Ok by Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 11/2000 - C.S. File 66/18-10

Ken Hoffine - For: Lone Rock Timber Co. - 3/2011 - M162-21  
-----  
Found - 1944 GLO gap  
13" D.Fir bears S.70¼°W., 29.4 ft (record S.71½°W., 29.6 ft) healed face and tag.  
41" D.Fir bears S.43½°E., 58.4 ft (record S.42°E., 57.4 ft) healed face and tag.  
28" D.Fir bears N.77½°E., 12.3 ft (record N.78°E., 12.7 ft) healed face and tag.  
11" Madrone bears N.56¾°W., 26.8 ft (rec N.56°W., 26.6 ft) healed face and tag.  
Corner lies on top of rocky ridge top.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 1/6/2022 (Filed 4/12/2022) - C.S. File 67/52-4  
-----  
Found - BLM brass cap projecting 12" above ground.  
41"x35' burnt-hollow I.Cedar N.78°E. 141.2 ft. 1940  
14"x3' sawn burnt Fir stump S.70¼°W., 29.9 ft. (rec. 29.4) healed blaze. 1966  
30"x9' broken burnt Fir snag S.43½°E., 57.3 ft. (rec. 58.4 ft) face burnt off. 1966  
28"x6' singed sawn Fir stump N.78°E., 12.3 ft. healed blaze. 1966  
11"x4' singed madrone stump N.56°W., 26.0 ft. (rec. N.56¾°W., 26.8 ft) 1966  
New - 17"x2½' tall sawn D.Fir stump N.35°W., 41.4 ft. 4" mag nail top center.  
Note - Monument is approx 125 ft SE'ly from sharp corner in forest access road.  
Area burnt 9/2020  
Compass decl. 14½°E.  
Lat: 43°24'26.05" N Long: 123°05'21.12" W