

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3724)

Set Fir post, 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on W. face, from which

A Fir 12" dia., bears N.11°W., 19 lks. mkd. 1/4 S BT.

A Dogwood 8" dia., bears N.28°E., 32 lks. mkd. 1/4 S BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11601)

Proportional measurement. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4
S7|S8
1944

from which

A Fir 12" dia., bears S.67°E., 49 lks., mkd. 1/4 S 8 BT.

A Fir 30" dia., bears West, 44 lks., mkd. 1/4 S7 BT.

Doug. County Surveyors Office - Vernon Tracy; Jack Heritage August 1966 - C.S. File 54/27-45

Found - Log 10 ft. long 48" dia., that undoubtedly lies on top of corner. GLO brass cap is probably buried under this log.

12" now 18" Fir, now stump S.67°E., 32.3 ft., shows good scar, we do not open.

30" now 46" Fir, west 29.0 ft. previously opened & shows "7" scribe.

New BTs- 9" D.Fir N.64°E., 33.9 ft. mkd. 1/4 S8 CS BT.

17" D.Fir N.15°W., 21.8 ft. mkd. 1/4 S7 CS BT.

This corner lies on steep, SW slope approx. 120 ft. N. of bottom of ravine, course NW.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 11/14/2000 - C.S. File 66/18-8

Found - 1944 GLO 2 1/2" brass cap on a 1" O.D. by 36" long iron pipe. BC/IP approx. 1 ft. under ground horizontal with no position, properly mkd.

Nail set recently by David Edwards at corner, from nail.

12" now 18" dia., 4 ft. high D.Fir stump with a fully healed single blaze, bears S.68 1/2°E., 32.3 ft. (Rec. S.67°E., 32.3 ft.) 1944

continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

30" now 49" dia., D.Fir with a fully healed single blaze bears N.87°W., 29.0 ft. (rec. West, 29.0 ft.) 1944

9" now 17" dia., D.Fir with a fully healed single blaze bears N.64°E., 33.9 ft. (agrees with rec.) 1966

17" now 24" dia., D.Fir with a fully healed single blaze, bears N.17¼°W., 21.8 ft. (rec. N.15°W., 21.8 ft.) 1966

Compass dec. 17½°E.

Set - 1944 BC/IP at position of nail, add stamping "DCSO RESET 2000" now marked:

¼
S 7 | S 8
DCSO
2000
1944

protrudes 5" out of ground and 2" above a small mound of stone.