

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6; 31 & 32 of T24-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, Under Contract #152 dated June 3, 1871 (DCSO records, Volume 7 Page 2944)

Set post cor. to secs. 5, 6, 31 and 32, from which

- A Hemlock 5" dia. bears N.52°E., 5 lks. dist.
- A Hemlock 6" dia. bears S.70°E., 8 lks. dist.
- A Hemlock 6" dia. bears S.81°W., 9 lks. dist.
- A Hemlock 5" dia. bears N.52°W., 10 lks. dist.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Pages 11531-32)

The original cor. of secs. 5, 6, 31 and 32, the locus of which has been perpetuated by the county surveyor's iron pipe, 3 ft. long 1" dia., firmly set in a small mound of stone. (Note: I found no source of record for this I.P. - V.L. 2/1992)

At point for corner, Set an iron post 3 ft. long 2" dia. 28" in the ground, with county surveyor's I.P. deposited at the base for cor. of secs. 5, 6, 31 and 32, with brass cap mkd.

T24S R3W
S31|S32
 S6|S5
 T25S
 1944

from which

- A Hemlock 12" dia. dead and down, bears S.70°E., 8 lks. dist., with no marks remaining on decayed face of old blaze. (old BT)
- A Hemlock 12" dia. dead and down, bears N.52°W., 10 lks. dist., with no marks remaining on decayed face of old blaze. (Old BT)
- A Fir 7" dia. bears N.25°E., 21 lks. dist. mkd. T 24S R 3 W S32 BT. (new BT)
- A Fir 6" dia. bears S.35½°E., 19 lks. dist. mkd. T 25 S R 3 W S5 BT. (New BT)
- A Hemlock 8" dia. bears S.46°W., 19 lks. dist., mkd. T 25 S R3W S6 BT. (New BT)
- A Fir 7" dia. bears N.70°W., 42 lks. dist. mkd. T 24 S R3W S31 BT. (New BT)

Greg Lang - For: Seneca Jones Timber Co. - April 2001 - M 138-6 & C.S. File 65/37-5I

Found - 1944 BLM brass cap properly mkd.
 22" Hemlock bears S.42 3/4°W., 13.1 ft. Price. Set spike in the base of the tree & placed new tag.

continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6; 31 & 32 of T24-3

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

18½" D.Fir bears S.34°E., 13.1 ft. Price. Set spike in the base of the tree & placed new tag.
14" D.Fir bears N.24½°E., 13.6 ft. Price. Set spike in the base of the tree & placed new tag.
New BTs- 15" D.Fir bears N.82¼°W., 42.0 ft. scribed "T24S R3W S31" "BT"Set spike in the base of the tree & placed new tag.
Set Alum. post at corner.
Note - On the top edge of a steep east'ly slope. Rock outcropping.

Fd. BC & 4 BTs by Ron Quimby, 12/2007 - M154-62