TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 240140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Bureau of Land Management Subdivision of Section - Wayne Rogers et al - Group #1386 - June 1987/Sept. 1988 (DCSO records, Volume 48 Pages 18500-01)

---

Point for the center ¼ sec. cor. of sec. 32, at intersection with the E. and W. center line.
Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd: T 25 S R 3 W
C¼ S 32
1988 from which
A B.Oak 15" dia., bears N.56°E., 368 lks. dist. mkd. C¼ S32 BT.
A B.Oak 10" dia., bears N.30¼°W., 493 lks. dist., mkd. C¼ S32 BT.
Deposit a white "DEEP-1" magnetic marker at the base of the
stainless steel post.
The corner is located in an open pasture.

Douglas Co. Surveyors Office - Crew: Jeff Lorsung- 11/27/2024 - C.S. File 67/59-19

---

Found - BLM brass cap (properly mkd) proj 6"
23" B.Oak N.56°E., 242.9 (rec. 368 lks)
17" B.Oak N.30¼°W., 325.4 ft. (rec. 493 lks)
Metal T. Post 2 ft. SW
Trees have new BT tag.
Note - Corner is in open pasture.
Compass decl. 14¼°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 189196.468 E 231534.537