

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 240340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

David Edwards - For: Roseburg Resources - 7/2002 - M 140-45

Set - 5/8"x36" steel pin w/alum. cap mkd: LS 2339 and 2002.
13" Fir N.76°E., 9.9 ft.
7" Fir S.44°E., 10.1 ft.
8" Fir S.47°W., 19.1 ft.
16" Fir N.25°W., 2.2 ft.
All scribed "C ¼ S20 BT"

Fd. 4 BTs & Alum. cap on IR by Ron Quimby, 3/2007 - C.S. 65/60-19

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 5/10/2022 (Filed 8/11/2022) - C.S. File 67/52-48

Found - 5/8" iron rod, 1" above ground
Baughman BT
Mostly burnt Cedar N.59¼°E., 18.8 ft.
DeGroot BTs
Burnt-sawn 17"x1/2" tall Fir stump S.16½°E., 21.7 ft (rec. S.15¼°E. 21.3) set 3" PK nail top center
5/8" iron rod S.63°00'42"W., 22.28 ft. proj. 4", cap gone.
5/8" iron rod N.14°49'22"W., 21.08 ft. proj. 5", cap gone.
New - 14"x8' tall burnt-sawn D.Fir stump, N.83°W., 2.6 ft. not blazed or scribed. 3" PK right side center. Metal lath south 2 ft.
Note - Area burnt 9/2020
Compass decl. 14½°E.
90° curve in road east ± 70 ft.
See sketch in file.
Lat: 43°22'49.41"N Long: 122°57'45.89"W