

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 240540

PRIMARY CORNER DESCRIPTION Center ¼ Sec 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

David Edwards - For: Roseburg Resources & Seneca Jones Timber Co. - Jan. 2001 - C.S. File 65/34-1B & M 136-33  
-----  
Set - 5/8" x 48" steel pin w/alum. "ROSEBURG RESOURCES" cap set.  
A 10" dia., Fir bears S.29°W., 6.07 ft.  
A 10" dia., Fir bears S.71°W., 12.05 ft.  
An 11" dia., Hemlock bears N.18°W., 7.50 ft.  
A 10" dia., Madrone, bears N.2°W., 3.00 ft.  
Note - BTs are described according to the 1972 BLM manual (and) measured to the center of tree at root crown.

Fd. Ok by R. Quimby 3/2/2007 - C.S. File 65/60-14

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 4/13/2023 - C.S. File 67/56-4  
-----  
Found - 2½" alum cap (properly mkd) on 5/8" iron rod, up 6". Singed 17" D.Fir S.75°W., 12.1 ft. (rec. S.71°W.) healed scar, add 3½" mag nail right side center.  
16"x0.5 ft sawn Hemlock stump, N.13°W., 7.2 ft. (rec. N.18°W., 7.5 ft) 3½" mag nail top center.  
10"x2 ft. sawn madrone stump N.2°W., 3.0 ft. 3½" mag nail top center.  
Steel post 1 ft south  
New - Sawn 12"x3½ ft. D.Fir stump, S.13½°E., 23.5 ft., 3½" mag nail top center.  
Note - Mon. at top of steep N slope at N edge flat ridge top.  
Area burnt 9/2020  
Compass decl. 14½°E.  
Lat: 43°24'54.21" N Long: 123°04'44.63" W