

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Laban H. Wheeler under Contract #467 dated April 7, 1883 (DCSO records, Volume 9 Page 3725)

Set Cedar post, 3 ft. long 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on N. face, from which
 A Cedar 18" dia. bears N.30°E., 31 lks. mkd. 1/4 S BT.
 A Hemlock 16" dia. bears S.81°W., 12 lks. mkd 1/4 S BT.

A. Boyer, Deputy Co. Surveyor - Wit: Tom Leatherwood; Ted Shelabarger - Jan. 25, 1939 - C.S. File 16/9

Located by running line from SW cor. to SE cor. Sec. 5.
 Set 3" sq. Yew post and scribed (blazed & scribed on bark)
 30" Fir S.12 1/2°E., 38.5 ft.
 28" Fir marked 1/4 S5 T25S R3W CS BT.
 30" Fir marked 1/4 S8 T25S R3W CS BT.
 28" Fir N.85 1/2°E., 23 ft.

GLO Dependent Resurvey by Norman D. Price under Special Instructions dated April 7, 1940 (DCSO records, Volume 27 Page 11602)

Found the 1/4 sec. cor., a Yew post, 4 ft. long 4" square, firmly set, mkd. 1/4 S5 CS on N., and 1/4 S8 on S. face.
 At point for corner, Set an iron post 3 ft. long 1" dia. 28" in the ground with county surveyor's marked stake deposited at the base, with brass cap mkd.

	S5
1/4	S8

	1944

from which
 A Fir 24" dia. bears N.85°E., 34 lks. dist. mkd. on bark 1/4 S5 T25S R3W CS BT. I reblaze & remark 1/4 S5 BT.
 A Fir 30" dia. bears S.13°E., 60 lks. dist., mkd. 1/4 S8 T25S R3W CS BT.

The 1/4 sec. cor. was established in 1939 by the county surveyor and duly recorded. I therefore accept it for control of this dependent resurvey.

Doug. Co. Surveyors Office - Ray Tracy; Jack Heritage
Sept. 1966 - C.S. 54/27-73

Found - GLO brass cap marked in 1944.
 24" now 38" Fir N.85°E., 22.4 ft. shows "1/4 S5T25S R3 BT" and very good scar.
 SE BT is now stump
 New BTs- 10" Hemlock S.66 1/2°E., 31.2 ft. mkd. 1/4 S8 CS BT.

continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

9" Hemlock N.55°E., 21.9 ft. mkd. ¼ S5 CS BT.
This corner lies on moderate NE slope approx. 220 ft. E. of
top of spur, sloping North.

Fd. & used on BLM dependent resurvey by Bryan S. Seibold,
Cadastral Surveyor, under Group #1800, surveyed July/Aug.
1996 - (DCSO records Vol. 52 Page(s) 19934)

Found OK by D. Edwards, Jan. 2001 - M136-33