

PRIMARY CORNER DESCRIPTION Center 1/4 Sec. 5

Alias	Description

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1800, surveyed July/Aug. 1996 - (DCSO records Vol. 52 Page(s) 19935)

Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line.

Set a stainless steel post, 28" long, 2½" diam., 26" in the ground, with brass cap mkd. T 25 S R 3 W

C ¼ S 5
1996

from which

A cedar, 10" diam., bears S.11½°W., 11½ lks. mkd. C¼ S5 BT.

A hemlock, 13" diam., bears S.69½°W., 19½ lks., mkd. C¼ S5 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this point, a point established by person(s) unknown, bears N.82°51'48"W., 0.015 chs., monumented with an iron pipe, 1¼" diam., firmly set, projecting 4" above ground, from which bearing trees mkd. by person(s) unknown:

A fir, 25" diam., bears N.51¾°E., 41 lks., with healed blaze.

A fir, 24" diam., bears S.48°E., 43½ lks., with healed double blaze.

A hemlock, 14" diam., bears S.21°W., 28 lks., with healed blaze.

Fd. BC & 3 BTs by Ron Quimby, 12/2007 - M154-62