TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias Description
Alias Description
Alias Description
Alias Description

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3702)

Set Hemlock post, 3 ft. long 3" square, 24" in ghe ground for ¼ sec.cor. mkd. ¼ S on W. face, from which

A Hemlock 8" dia., bears N.20°W., 16 lks. dist., mkd. ¼ S BT.

A Fir 6" dia., bears N.36°E., 27 lks. dist., marked ¼ S BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Pages 11575-78)

Proportional Measurement. Set an iron post 3 ft. long 1" dia., 28" in the ground for ¼ sec. cor., with brass cap marked: ¼

S32|S33

1943

from which

A Yew 8" dia., bears S.8½°E., 42 lks. dist., mkd. ¼ S 33 BT.

A Fir 42" dia., bears S.61½°W., 48 lks. dist., mkd. ¼ S32 BT.

BLM Dependent Resurvey, by Rogers, etal under Group #1386 July 1987/Sept. 1988 (DCSO records, Volume 48 Page 18482)

From the ¼ sec. cor. of secs. 32 and 33, monumented with an iron post, 2" dia., firmly set, projecting 7" above ground, with a GLO 1943 brass cap.

from which a bearing tree mkd. by Price

A Yew 10" dia.,bears S.8½°E., 42 lks. dist., with fragmentary scribe marks visible on partiall healed blaze.

and and new bearing tree

A Fir 12" dia., bears N.50°W., 50 lks. dist., mkd. ¼ S32 BT.