

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 & 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3704)

-----  
 Set Yew post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 20, 21, 28 and 29 mkd. T25S S21 on NE., R3W S28 on SE., S29 on SW. and S20 on NW. faces, with 2 notches on S. and 4 notches on the E. edges, from which  
     A Fir 30" dia., bears N.65°E., 30 lks. dist., mkd.  
         T25S R3W S21 BT.  
     A Fir 30" dia., bears S.60°E., 40 lks. dist., mkd.  
         T25S R3W S28 BT.  
     A Fir 36" dia., bears S.69½°W., 31 lks. dist., mkd.  
         T25S R3W S29 BT.  
     A Fir 24" dia., bears N.82°W., 67 lks. dist., mkd.  
         T25S R3W S20 BT.

GL0 Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Pages 11578-79)

-----  
 Point for original cor. of secs. 20, 21, 28 and 29, determined at the mean position of the record measurements from the original NE., SE., and SW. bearing trees. At point for corner, set an iron post, 3 ft. long, 2" dia., 28" in the ground for cor., with brass cap mkd.

T25S R3W	S20	S21
	S29	S28
	1943	

1943 from which  
 A dead Fir 30" dia., bears N.44°E., 44 lks. dist., with partial scribe marks on old bark blaze. (Old BT)  
 A Fir 56" dia., bears S.44°E., 40 lks. dist., on which the old bark blaze has sloughed off and only faint ax marks were found. I re-blaze and re-mark this old bearing tree T25S R3W S28 BT.  
 A Fir 32" dia., bears S.45 3/4°W., 45 lks. dist., with partial scribe marks on old bark blaze. I re-blaze and re-mark this old bearing tree T25S R3W S29 BT.  
 A red Cedar 12" dia., bears N.11°E., 51 lks. dist., mkd.  
     T25S R3W S21 BT. (New BT)  
 A Hemlock, 6" dia., bears S.28°E., 17 lks. dist., mkd.  
     T25S R3W S28 BT. (New BT)  
 A Red Cedar 16" dia., bears S.27¼°W., 70 lks. dist., mkd.  
     T25S R3W S29 BT. (New BT) (New BT)  
 A Hemlock 8" dia., bears N.14°W., 18 lks. dist., mkd.  
     T25S R3W S20 BT. (New BT)

continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21 28 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>Doug. County Surveyors Office - Vernon Tracy; Jack Heritage July 1966 - C.S. File 54/27-28 ----- Found - 1943 GLO brass cap mkd. All BTs as of 1943 resurvey are gone, down or stumps, badly burned &amp; rotted. No scribe marks found. New BTs - 3" Hemlock N.42°W., 3.5 ft. mkd. S20 CS BT. 4" Hemlock S.9½°E., 25.5 ft. mkd. S28 CS BT. 4" D.Fir S.74°W., 6.0 ft. mkd. S29 CS BT. 4" D.Fir N.34°E., 25.4 ft. mkd. S21 CS BT. Steel fence post set alongside brass cap. Corner lies approx. 100 ft. north of corner of timber in dense reproduction of D.Fir and Hemlock.</p>
<p>Fd. 4 BTs &amp; GLO BC by Ron Quimby, 3/2007 - C.S. 65/60-20</p>
<p>Ron Quimby - For: Roseburg Resources - March 2015 - M166-32 ----- Found - 1943 GLO brass cap 48" tall, 12" fir snag N.34°E., 25.4' healed scar 16" hemlock S.9°E., 25.5' healed scar 10" fir S.74°W., 6.0' healed scar 16" hemlock N.42°W., 3.5' healed scar</p>
<p>Fd OK per rec 9/2020 R Quimby - Area burnt - C.S. 65/106-62</p>
<p>Douglas Co. Surveyors Office - Crew: Stephen Flause &amp; Jeff Lorsung- 4/25/2022 (Filed 7/20/2022) - C.S. File 67/52-35 ----- Found - 2½" GLO brass cap (properly mkd) on 1¾" ID I.pipe proj. 13" 20"x1 ft. Burnt sawn Hemlock stump S.9°E., 25.5 ft. Burnt-dead 12" Fir S.74°W., 6.4 ft. (rec 6.0 ft) healed scar. 17" Hemlock N.42°W., 3.5 ft healed scar, singed. Steel fence post SSE 2.5 ft from brass cap. New - Burnt-sawn 19"x1½ ft D.Fir stump N.12°E. 8.4 ft., PK top center. Note - Add 3" PKs to right side center of BTs Area burnt 9/2020 Compass decl. 14½°E. See sketch in file Lat: 43°22'42.16"N Long: 123°04'09.90"W</p>