

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3706)

Set Yew post 4 ft. long, 4" sq., 24" in the ground for Cor. to secs. 16, 17, 20 and 21, mkd. T25S S16 on NE., R3W S21 on SE., S20 on SW., and S17 on NW. faces, with 3 notches on S. and 4 notches on E. edges, from which
A Fir 40" dia, bears N.60°E., 35 lks mkd T25S R3W S16 BT
A Fir 36" dia, bears S.20°E., 24 lks mkd T25S R3W S21 BT
A Hemlock 10" dia., bears S.50°W., 18 lks., mkd. T25S R3W S20 BT
A Cedar 24" dia., bears N.21°W., 11 lks. mkd. T25S R3W S17 BT.

GL0 Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Paged 11580-81)

Point for original cor. of secs. 16, 17, 20 and 21, determined at the record distance from each of the orig. BTs At point for corner, set an iron post, 3 ft. long 2" dia., 28" in the ground, for cor. of secs., with brass cap mkd.

T25S R3W
S17 S16

S20 S21

1943

from which

- A Fir 50" dia., bears N.29°E., 35 lks. dist., mkd. on bark BT T25S R3 S16. (Old BT)
- A Fir 40" dia., bears S.68°E., 24 lks. dist., mkd. on bark T25 R3 S21 BT. (Old BT)
- A Hemlock 16" dia., bears S.29¼°W., 18 lks. dist., with blaze healed. (Old BT)
- A Red Cedar 28" dia., bears N.74°W., 11 lks. dist., with blaze healed. I re-blaze and re-mark this old bearing tree T25S R3W S17 BT.
- A Fir 54" dia., bears N.74°E., 57 lks. dist., mkd. T25S R3W S16 BT. (New BT)
- A Yew 6" dia., bears S.15½°E., 33 lks. dist., mkd. T25S R3W S21 BT. (New BT)

This sec. cor. is located on top of a ridge, bears NW & SE.

Doug. County Surveyors Office - Vernon Tracy; Jack Heritage August 1966 - C.S. File 54/27-41

Found - GL0 brass cap, 1943, with steel fence post set alongside.

Continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

All BTs called for in field notes are now destroyed by logging. Stumps & snags remain.

New BTs- 6" D.Fir S.35°W., 15.3 ft. mkd. T25S R3W S20 CS BT.
5" Chinquapin S.76°E., 9.6 ft. mkd. S21 CS BT.
50" Fir stump N.29°E., 23.1 ft. (orig. BT) rescribed "T25S R3W S16 CS BT".
No other trees suitable.

Found Brass cap and 5 BTs, Burton Holt, August 1980 -C.S. File 58/163

Mark Smalley - For: Roseburg Resources - 1/2002 - C.S. File 65/42-1

Found - 1943 US GLO 2" IP with 2½" brass cap, properly mkd.
50" D.Fir stump bears N.29°E., 23.1 (OBT)
20" D.Fir - good condition - bears S.35°W., 15.3

New - 10" D.Fir bears N.64°E., 22.0 scribed "S16 BT"
9" D.Fir bears S.41°E., 12.3 scribed "S21 BT"
12" D.Fir bears N.20°W., 7.6 scribed "S17 BT"

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 6/15/2021 (Filed 4/7/2022) - C.S. File 67/51-31

Found - 2" IP with 2½" brass cap, US GLO 1943, projects 10".
Burnt 40"x2½" D.Fir stump N.29°E., 23.1 ft.
26"x7' D.Fir stump S.39°W., 14.5 ft. (rec. S.35°W., 15.3 ft.)
11"x6' D.Fir stump N.61°E., 22.7 ft. (rec. N.64°E., 22.0 ft.)
11"x6' D.Fir stump S.37°E., 12.0 ft. (rec. S.41°E., 12.3 ft.)
14"x7' D.Fir stump N.22°W., 8.5 ft. (rec. N.20°W., 7.6')

All stumps show good scars but burnt.

New - Metal Fence post north 2 ft.
Note - area burnt 9/2020
Compass decl. 14¾°E.
Lat: 43°23'39.50" N 123°04'11.07" W