

PRIMARY CORNER DESCRIPTION 1/4 Corner for Secs. 16 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3707)

Set Yew post, 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on W. face, from which

A Fir 6" dia., bears N.25°E., 20 lks., mkd. 1/4 S BT.

A Fir 8" dia., bears N.75°W., 33 lks., mkd. 1/4 S BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11582)

Proportional measurement. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4
S17|S16
1943

from which

A Fir 16" dia., bears N.30°E., 56 lks., mkd. 1/4 S16 BT.

A Fir 22" dia., bears N.15°W., 19 lks., mkd. 1/4 S17 BT.

Doug. County Surveyors Office - Vernon Tracy; Jack Heritage August 1966 - C.S. File 54/27-43

Found - GLO brass cap mkd. 1944, with steel fence post alongside.

16" now 21" D.Fir N.30°E., 37.0 ft. shows good scar. Do not open. Alive.

22" now 29" D.Fir N.15°W., 12.5 ft. shows good scar. Do not open. Alive.

Since both BTs above are of usable size, mark new trees:

8" Hemlock N.69°E., 1.3 ft. mkd. 1/4 S16 CS BT.

15" R.Cedar S.7°W., 30.1 ft. mkd. 1/4 S17 CS BT.

Corner lies on NW slope approx. 130 ft. south & 50 ft. east of creek, course NE.