

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Laban H. Wheeler under Contract #467 dated April 7, 1883 (DCSO records, Volume 9 Page 3710)

Set Yew post, 4 ft. long, 4" sq. 24" in the ground for cor. to secs. 4, 5, 8 and 9, mkd. T25S S4 on NE., R3W on SE., S8 on SW. and S5 on NW. faces, with 5 notches on S. and 4 notches on E. edges, from which

- A Fir 6" dia. bears N.81°E., 30 lks. mkd. T25S R3W S4 BT.
- A Cedar 24" dia. bears S.10°E., 24 lks. mkd T25S R3W S9 BT
- A Maple 6" dia. bears S.59°W., 11 lks. mkd. T25S R3W S8 BT
- A Fir 8" dia. bears N.41°W., 11 lks. mkd. T25S R3W S5 BT.

A. Boyer, Deputy Co. Survey - Wit: Floyd Norris; Clint Bamber June 1939 C.S. File 16/29; C.S. File 35/38 and Vol. 4 Pg. 80 and ("Old" Renewal Vol. 1 Page 50)

BT, S10°E., 24 lks., which is now laying on ground and stump still standing. Set 4" x 4" Laurel post for cor. from which

- 8" Fir bears N.60°W., 23.5 ft. mkd. S5 T25S R3W CS BT.
- 10" Fir bears N.31°E., 30.0 ft. on slope, marked S4 R3W C. S. BT.
- 36" Fir bears N.81°E., 79.0 ft. on slope scribe marks by some CS still show on blaze (no record of this tree)
- 24" Fir bears S.39°E., 118.0 ft. on slope, marked S9 T25S R3W CS BT.
- 40" Fir bears South 78.0 ft. on slope marked S8 T25S R3W CS BT and marked low a/c logging operations and barked blazed and scribed.

GLO Dependent Resurvey by Norman D. Price, under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Pages 11585-86)

Found the original cor. of secs. 4, 5, 8 and 9, the locus of which has been perpetuated by the county surveyor's Yew post, 4 ft. long, 4" sq. firmly set, mkd. T25S S4 on NE., R3W S9 on SE., S8 on SW., and S5 CS on NW. face.

At point for corner, set an iron post, 3 ft. long, 2" dia. 28" in the ground with county surveyor's marked stake deposited at the base, for cor., with brass cap mkd:

```

T25S R3W
  S5|S4
  S8|S9
    1944

```

from which

- A Cedar stump 36" dia. bears S.10°E., 24 lks., on which only ax marks remain. (Old BT)

continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 40" dia. bears N.84½°E., 110 lks., with partial scribe marks visible on portion of old blaze which has been previously uncovered. (A bearing tree marked by the Co. Surveyor in 1914)

Other bearing trees marked by the county surveyor in 1939, the blazes on which are covered with pitch and almost overgrown, stand as follows:

- A Fir 14" dia. bears N.35¼°E., 41 lks. dist.
- A Fir 24" dia. bears S.35½°E., 177 lks. dist.
- A Fir 54" dia. bears S.2½°W., 121 lks. dist.
- A Fir 10" dia. bears N.57½°W., 33 lks. dist.

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1800, surveyed July/Aug. 1996 - (DCSO records Vol. 52 Page(s) 19932)

Found OK by D. Edwards, Jan. 2001 - M136-33

2