

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 9 Page 3663)

Set Qr. sec. post, from which
A Red Fir 10" dia., bears S.85°E., 173 lks. dist.
A W.Oak 4" dia., bears N.79°E., 185 lks. dist.

GLO Dependent Resurvey by Norman D. Price, Under Special
Instructions dated April 5, 1940 (DCSO records, Volume 27
Page 11504)

Point for original 1/4 se.cor., determined at the record bearing
and distance from the original SE bearing tree.
At point for corner, Set an iron post, 3 ft. long 1" dia., 28"
in the ground, for 1/4 sec. cor., with brass cap marked:

1/4 S33

S4

1943

from which

A Fir 40" dia., bears S.85°E., 173 lks. dist., on which
I uncovered the scribe marks 1/4 S beneath 88 years
overgrowth. (Old BT)

A Fir 12" dia., bears N.52 3/4°W., 27 lks. dist., mkd. 1/4
S 33 BT. (New BT)

A Fir 12" dia., bears S.10 3/4°W., 16 lks. dist., marked

Doug. Co. Surveyors Office - Vernon Tracy; Mike Stone; J.
Layne - Feb. 1, 1966 - C.S. File 54/7-39

Found - 1943 GLO brass cap for corner.
Orig. 42" D.Fir S.85°E., 114.2 ft. (face) previously
opened, face pitched over.
12" now 18" D.Fir N.52 3/4°W., 17.8 ft., shows very
good scar.
12" now 14" D.Fir S.10 3/4°W., 10.6 ft., shows good
scar, fence wire wrapped around BT & grown over
New BT - 9" D.Fir S.51°W., 22.3 ft. mkd. 1/4 S4 CS BT.

Fd. Ok - Herman Pieske - Jan. 21, 1994 - M118-33

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 11/6/2007 - C.S. File 67/24-44

Found, orig. 42" D.Fir (S.85°E., 114.2 ft) now 50 ft. tall
snag. Both 1943 ren. trees alive & healthy. 1966 ren tree
(S.51°W., 2213 ft.) now 25 ft. tall snag.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 33; & 4 of T 26-3

Alias	Description

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W. Saveland, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCSO records Vol. 57 Page(s) 22415)

The ¼ sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1966, monumented with an iron post, 1 in. diam., firmly set, projecting 9" above ground, with brass cap (properly) mkd. from which the remains of an original bearing tree

A fir snag, broken at base, 48" dia., bears S.85°E., 117.4 ft., with fragmentary scribe marks visible on a broken open, weathered blaze. (Record, 114.2 ft.) and bearing trees mkd. by Price

A fir, 16" dia., bears S.10¾°W., 10.6 ft., with a healed blaze.

A fir, 22" dia., bears N.52¾°W., 17.8 ft., with a healed blaze.

and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office

A fir snag, 8" dia., bears S.48°W., 21.6 ft., with fragmentary scribe marks visible on a partially healed blaze.

Corner is located on a S. slope, N., 10 ft. from the approximate intersection of a woven and barbed-wire fence line extending S. and a barbed-wire fence line extending E.

Adam DeGroot - For: Dollens & Strader - Dec. 2020 - M178-27

Found - A 1" iron post by Price in 1943 firmly set & projecting 9" above the ground with a 2½" brass cap properly mkd per the record:

A 16" D.Fir bears S.11°30'W., 10.2 ft w/healed blaze (S.10¾°W., 16 lks) 1943

A 23" D.Fir bears N.51°45'W., 17.1 ft w/healed blaze (N.52¾°W., 27 lks) 1999

New BTs- A 28" D.Fir bears N.84°15'E., 24.4 ft scribed "¼ S33 BT" on dbl blaze

A 18" D.Fir bears S.84°45'W., 27.8 ft scribed "¼ S4 BT" on dbl blaze

Note - Corner falls in E-W fence line in low intensity burn area

BTs are alive and trunks charred 15-20 feet high