TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3705)

Set Yew post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
A Fir 36" dia., bears N.50°E., 14 lks. mkd. ¼ S BT.
A Maple 5" dia., bears S.15°E., 30 lks., mkd.¼ S BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11579)

Point for original ¼ sec. cor., determined at the record bearing and distance from the original NE. bearing tree. At point for cor. set an iron post, 3 ft. long 1" dia., 28" in the ground, for ¼ sec. cor. with brass cap mkd.

¼ S21 / S28
1943

from which
A Fir 40" dia., bears N.50°E., 14 lks. dist., with partial scribe marks on old bark blaze. I re-blaze and re-mark this old bearing tree ¼ S21 BT.
A Fir 16" dia., bears S.80°W., 49 lks. dist., mkd. ¼ S28 BT. (New BT)

Carl Sweeden - April 19, 2004 - C.S. File 65/49-28

Found - 1943 2½" BC on iron post, up 0.8' at bottom of 50-60' vert. rock wall.
40" D.Fir BT, N.49°E., 9.24', healed dbl blaze, scar vis. tag.
16" now 31" D.Fir BT, S.80°W. 32.34', double blazed, scar vis. tag.
New BT - 14" Hemlock BT, N.40°W. 26.83', scribed "S ¼ S21 BT" tag.
Note - Corner located approx. 6' North of 50'-60' vert. wall.

Ron Quimby - For: Roseburg Resources - March 2015 - M166-32

Found - 1943 GLO brass cap
43" Fir N.49°E., 9.2' healed scar
34" Fir S.80°W., 32.3' healed scar
14" Hemlock N.40°W. 26.8' standing dead/healed scar
New BTs- 25" Fir N.72°W., 29.9'
18" Hemlock N.10°W., 29.0' both scribed "¼ S28 BT"