

PRIMARY CORNER DESCRIPTION 1/4 Cor to Secs. 9 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3709)

Set Cedar post, 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on N. face, from which
A Maple 8" dia., bears S.16°E., 23 lks., mkd. 1/4 S BT.
A Fir 6" dia., bears N.33°W., 17 lks., mkd. 1/4 S BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11584)

Proportional measurement.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor, with brass cap mkd: $\frac{S9}{1944}$
1/4 S16

from which
A Fir 8" dia., bears N.10°E., 26 lks., mkd. 1/4 S9 BT.
A Fir 12" dia., bears S.42°W., 63 lks., mkd. 1/4 S16 BT.

Doug. County Surveyors Office - Vernon Tracy; Joe Brady; Jack Heritage - July/Aug. 1966 - C.S. File 54/27-50

Found - GLO brass cap mkd. 1944, with steel fence post alongside.
8" now 16" D.Fir N.10°E., 17.2 ft., previously opened & shows "B" scribe. Alive.
12" now 21" W.Fir S.42°W., 41.6 ft. fragmentary scribe visible on badly injured blaze.
New BTs - 8" R.Cedar N.22°E., 9.2 ft. mkd. "1/4 S9 CS BT".
7" D.Fir S.15°E., 16.9 ft, mkd. "1/4 S16 CS BT".
Brass cap lies between two rotted logs in young fir and hemlock timber.

Found brass cap and four BTs - BLM Dependent Resurvey by Rogers et al - June 1987/Sept. 1988 - (DCSO records, Vol. 48 Pages 18483-84)

Douglas Co. Surveyor's Office - Crew: Stephen Flause & Mike Koch - 7/21/2016 - C.S. File 67/44-25

Found - A 1" iron post by Price, 1944, firmly set, projecting 12" above the ground with a 2 1/2" dia. brass cap (properly) marked

continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor to Secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BTs by Price in 1944 - A 16" dia. x 12" tall sawn D.Fir stump bears N.10°E., 17.2 ft. with no blaze evidence remaining

A 30" dia. x 36" tall hemlock stump bears S.42°W., 41.6 ft. Opened to find scribe marks "BT" visible.

BTs by Tracy, in 1966 per C.S.54/27 - A 9" dia. x 9" tall sawn R.Cedar stump bears N.19¼°E., 9.2 ft. with fragmentary scribe marks visible on a partially healed blaze.

New BT - A 5" dia. D.Fir bears N.78½°E., 18.4 ft. scribed "X CS BT".

A 6" dia. D.Fir bears S.34½°E., 22.6 ft. scribed "¼ S16 CS BT".

A 7" dia. D.Fir bears S.49½°W., 28.1 ft. scribed "¼ S16 CS BT".

A 7" dia. D.Fir bears N.81¼°W., 8.3 ft. scribed "¼ S9 CS BT".

Location & comments - All BTs have BT tags attached. All new BTs have double blazed faces with bearings measured to the center of the tree at the root crown and distances measured to the side and center of the root crown.

The corner falls on a gentle NW slope at the foot of a steep NW slope in young fir and hemlock reprod. (See vicinity sketch in attached notes)

Compass declination: 15°E.