

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 340540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Bureau of Land Management Survey, Subdivision of Section
by Wayne Rogers, etal - Group #1386 - Survey, June 1987
Sept. 1988 (DCS0 records, Volume 48 Page 18497)

Point for the center ¼ sec. cor. of sec.9, at intersection
with the E. and W. center line.

Set a stainless steel post, 28" long, 2½" dia., 24" in the
ground, with brass cap mkd. T 25 S R 3 W

C ¼

S 9

1987

from which

A Fir 6" dia., bears S.48½°E., 7 lks. dist., mkd.

C¼ S9 BT.

A Hemlock 16" dia., bears S.23½°W., 19½ lks. dist., mkd.

C¼ S9 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the
stainless steel post.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 10/12/2021 (Filed 11/23/2021) - C.S. File 67/51-17

Found - (BLM 1987) 3¼" brass cap 6" above ground.

Root only of 16" Hemlock S.23½°W., 12.9 ft.

New - 23"x3 ft. burnt fir stump 4" MAG NAIL top center
with DOUGLAS CO. SURVEYOR brass washer

N.84°E., 41.8 ft.

27"x3 ft. burnt fir stump 4" MAG NAIL & brass
washer DOUGLAS CO. SURVEYOR top center
S.56°E., 30.0 ft.

16" burnt Hemlock face with alum nail & brass
washer DOUGLAS CO. SURVEYOR 4" MAG NAIL &
steel washer DOUGLAS CO. SURVEYOR in root
crown S.76°W., 20.0 ft

20" burnt Hemlock N.41½°W., 33.0 ft alum nail &
brass washer in face 4" MAG NAIL & steel
washer in root crown.

Note - Moderate North slope burnt clear cut to East &
South burnt old second growth NW quad.

Area burnt 9/2020

Compass decl. 14½°E.

Lat: 43°24'56.48" N Long: 123°03'29.76" W