TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 340640

PRIMARY CORNER DESCRIPTION Center ¼ sec. cor. Sec. 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A. Boyer, Co. Surveyor - For: Young & Co. Bank - Wit: Crear; Hughes and Williams. - Vol. 4 Pg. 80; C.S. File 35/38 - Oct. 1941

Set 4" x 4" post, from which
A Cedar 8" bears N.55°E., 9.0 ft.
A R.Fir 10" bears S.63°W., 9.5 ft.

Bureau of Land Management Resurvey - Rogers, Bedell and Peterson - Group #1386 - Survey June 1987 - Sept. 1988 (DCSO records, Volume 48 Pages 18493-94)

The center ¼ sec. cor. of sec. 4, established and recorded by Arthur Boyer in 1941, and is accepted as the corner, determined from the remaining bearing tree mkd by Boyer:

A Hemlock 16" dia. bears S.63°W., 14½ lks. dist., with scribe marks CEN S4 T25 R3 visible on opened blaze.

At the corner point, set a stainless steel post, 28" long 2½" dia., 22" in the ground with brass cap mkd: T 25 S
R 3 W
C 1/4
S 4
1987

from which new bearing trees:

A Hemlock 15" dia. bears N.57°E., 16 lks. dist. mkd. C ¼ S4 BT.

A Cedar, 11" dia. bears S.11°E., 9 lks. dist. marked C ¼ S4 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.