

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3692)

Set Hemlock post, 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 27, 28, 33 and 34, mkd. T25S S27 on NE., R3W S34 on SE., S33 on SW., and S28 on NW faces, with 1 notch on S. and 3 notches on E. edges, from which

- A Chinquapin 8" dia., bears N.65°E., 33 lks. dist., mkd. T25S R3W S27 BT.
- A Chinquapin 8" dia., bears S.85°E., 20 lks. dist., mkd. T25S R3W S34 BT.
- A Chinquapin 6 dia., bears S.55°W., 14 lks. dist., mkd. T25S R3W S33 BT.
- A Chinquapin 6" dia., bears N.60°W., 23 lks. dist., mkd. T25S R3W S28 BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11564)

Point for original cor. of secs. determined by reference to the record measurements from the old NE., SE., and SW. BTs. At point for corner, set an iron post, 3 ft. long, 2" dia., 28" in the ground for cor. with brass cap mkd. T25S R3W

S28	S27
S33	S34
1943	

from which

- A Chinquapin 8" dia., dead and down, bears N.62°E., 33 lks. dist., with partial scribe marks on decayed face of old blaze. (Old BT)
- A Chinquapin 8" dia., dead and down, bears S.84°E., 20 lks. dist., with partial scribe marks on decayed face of old blaze. (Old BT)
- A Chinquapin 8" dia., dead and down, bears S.56°W., 14 lks. dist., with partial scribe marks on decayed face of old blaze. (Old BT)
- A Fir 20" dia., bears N.32°E., 94 lks. dist., mkd. T25S R3W S27 BT. (New BT)
- A Fir 36" dia., bears S.61 3/4°E., 76 lks. dist., mkd. T25S R3W S34 BT. (New BT)
- A Fir 20" dia., bears S.84°W., 28 lks. dist., mkd. T25S R3W S33 BT. (New BT)
- A Fir 26" dia., bears N.31°W., 36 lks. dist., mkd. T25S R3W S28 BT. (New BT)

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Doug. County Surveyors Office - Vernon Tracy; Joe Brady;
Jack Heritage - June/July 1966 - C.S. File 54/27-8

Found - 1943 GLO brass cap mkd.
No trace of orig. 1883 BTs. 1943 resurvey BTs as follows:
20" now 30" Fir N.32°E., 62.0 ft., now snag with
healed blaze.
36" now 44" Fir S.61 3/4°E., 50.2 ft. Alive, shows
good scar.
NW and SW BTs now stumps.
New BTs - 16" D.Fir N.24 1/2°W., 47.4 ft. mkd. T25S R3W S28 CSBT.
16" D.Fir N.14°E., 72.5 ft. mkd. T25S R3W S27 CS BT.
No trees available to SW.
Corner lies on N-S cutting line, cut off to west.

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W.
Saveland, Cadastral Surveyors and Robert H. Browning, Survey
Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCSO
records Vol. 57 Page(s) 22436-7)

The cor. of secs. 27, 28, 33, and 34, perpetuated by the
Douglas County Surveyor's Office in 1966, monumented with an
iron post, 2" dia., firmly set, projecting 2" above ground,
with brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Price

A sawed, decayed fir stump, size indeterminate, bears
N.32°E., 62.0 ft., with scribe mark T visible on a
partially healed blaze.

A sawed, decayed fir stump, size indeterminate, bears
S.61 3/4°E., 50.2 ft., with axe marks visible.

A decayed fir stump, size indeterminate, bears S.84°W.,
18.5 ft., with no marks visible.

A decayed fir stump, size indeterminate, bears N.31°W.,
23.8 ft., with no marks visible.

and the remains of bearing trees mkd. by the Douglas County
Surveyor's Office

A sawed fir stump, 19" dia., bears N.13°E., 73.4 ft.,
with scribe marks CS BT visible on a partially
healed blaze.

A sawed fir stump, 23" dia., bears N.25 3/4°W., 47.1 ft.,
with no marks visible.

and new bearing trees

A fir, 9" dia., bears N.66 1/4°E., 17.9 ft., mkd. T25S R3W
S27 BT.

A fir, 9" dia., bears S.84 1/2°E., 8.9 ft., mkd. T25S R3W
S34 BT.

continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 8" dia. bears S.49°W., 10.6 ft mkd. T25S R3W S33 BT
A fir, 9" dia. bears N.46°W., 20.4 ft mkd. T25S R3W S28 BT
Corner is located on a broken S. slope.