

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3695)

Set Hemlock post 3 ft. long 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on W. face, from which
A Fir 30" dia., bears N.20°E., 73 lks. dist.,
mkd. 1/4 S BT.
A Fir 6" dia., bears N.31°W., 92 lks. dist., mkd.
1/4 S BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Pages 11567-68)

Proportional measurement. Set an iron post, 3 ft. long, 1" dia., 16" in the ground to bedrock, and in a mound of stone to top for 1/4 sec. cor., with brass cap mkd.

1/4
S21|S22
1943

from which

A Fir 32" dia., bears N.59°E., 47 lks., mkd. 1/4 S22 BT.
A Hemlock 14" dia., bears N.5°W., 58 lks. mkd. 1/4 S21 BT.

Doug. County Surveyors Office - Vernon Tracy; Jack Heritage August 1966 - C.S. File 54/27-47

Found - GLO brass cap in mound of stone, mkd. 1943, with steel fence post alongside & stump of one BT as follows:

32" now 34" Fir N.59°E., 31.0 ft. shows "1/4 S BT" scribe on partially healed blaze. Now stump.

New BTs - 10" Hemlock N.18°E., 25.8 ft. mkd. 1/4 S22 CS BT.
11" Hemlock N.70°W., 62.7 ft. mkd. 1/4 S21 CS BT.