

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 & 22

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3695)

 Set Dogwood post, 4 ft. long, 4" sq., 2 ft. in the ground for sec. cor. to 15, 16, 21 and 22, mkd. T25S S15 on NE., R3W S22 on SE., S21 on SW., and S16 on NW. faces, with 3 notches on S. and E. edges, from which

- A Fir 20" dia., bears N.28°E., 37 lks. dist., mkd. T25S R3W S15 BT.
- A Fir 30" dia., bears S.43°E., 74 lks. dist., mkd. T25S R3W S22 BT.
- A Fir 18" dia., bears S.71°W., 19 lks. dist., mkd. T25S R3W S21 BT.
- A Fir 36" dia., bears N.21°W., 70 lks. dist., mkd. T25S R3W S16 BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11568)

 Point for orig. cor. of secs. 15, 16, 21 and 22, determined by reference to the record bearing and distance from the original SE bearing tree. At point for corner, set an iron post 3 ft. long 2" dia., 28" in the ground, for corner, with brass cap mkd.

T25S R3W
S16|S15
 S21|S22

1943

from which

- A Fir 16" dia., bears S.43°E., 74 lks. dist., on which I uncovered the scribe marks T25 SW S22 BT beneath 60 years overgrowth. (Old BT)
- A Fir 14" dia., bears N.30°E., 22 lks. dist., mkd. T25S R3W S15 BT. (New BT)
- A Fir 16" dia., bears S.12°E., 20 lks. dist., mkd. T25S R3W S22 BT. (New BT)
- A Fir 18" dia., bears S.61¼°W., 38 lks. dist., mkd. T25S R3W S21 BT. (New BT)
- A Fir 20" dia., bears N.32½°W., 6 lks. dist., mkd. T25S R3W S16 BT. (New BT)

Doug. County Surveyors Office - Vernon Tracy; Jack Heritage Sept. 1966 - C.S. File 54/27-78

 Found - GLO brass cap mkd. in 1943 with steel fence post set alongside. (Cont. Next Page)

TOWNSHIP 25 RANGE -3 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

| | | | |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

16" Fir, now snag, S.12°E., 13.2 ft., shows scribe on unhealed blaze.
18" Fir, now snag, S.61¼°W., 25.1 ft., shows scribe on unhealed blaze.
20" Fir now shattered snag, N.32½°W., 4.0 ft., scribed face lying face down, fragmentary reverse scribe visible.
Other bearing trees gone.
New BTs - 12" Red Cedar N.5°W., 30.5 ft. mkd. T25S R3W S16 CS BT.
16" Hemlock N.38°E., 38.0 ft. mkd. T25S R3W S21 CSBT
9" Hemlock S.64°W., 29.5 ft. mkd. T25S R3W S21 CSBT.
4" Hemlock S.61°E., 15.4 ft. mkd. S22 CS BT.

2