

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 440140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W. Saveland, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCSO records Vol. 57 Page(s) 22442)

-----  
Point for the center ¼ sec. cor. of sec. 34, at intersection with the E. and W. centerline.  
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T25S R3W  
C ¼ S 34  
2008

from which  
A fir, 9" dia., bears N.78¾°E., 24.1 ft., mkd. C ¼ S34 BT.  
A cedar, 7" dia. bears N.18¾°W., 14.4 ft. mkd. C ¼ S34 BT.  
Deposit a magnet in a white plastic case at the base of the stainless steel post.  
Corner is located E., 185 ft. from a dirt road, 11 ft. wide, bears N.10°W. and S.25°E., in curve.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 5/31/2023 - C.S. File 67/56-28

-----  
Found - No monument found, gone due to logging.  
Burnt-sawn, 10"x1' D.Fir stump, N.78¾°E., 24.1 ft., part of lower blaze add 3½" mag nail top center.  
Burnt-sawn, 6"x10" cedar stump N.18¾°W., 14.4 ft. part of lower blaze add 3½" mag nail top center.  
New - 5/8"x30" iron rod with DCSO yellow plastic cap set at record distance from found BTs, cap up 7"  
Note - Corner is E 185' from dirt road 11' wide bears N.10°W. And S.25°E. in curve.  
Area burnt 9/2020  
Compass decl. 14½°E.

Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
189107.037 N 242009.200 E