

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3696)

Set Cedar post, 4 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on N. face, from which
A Hemlock 20" dia., bears N.44 1/2°E., 15 lks. dist., mkd. 1/4 S BT.
A Hemlock 16" dia., bears S.55°W., 23 lks. dist., mkd. 1/4 S BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11569)

Point for original 1/4 sec. cor., determined by reference to the record measurements from both original bearing trees. At point for corner, set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4 S15
 S22
 1943

from which
A Hemlock 25" dia., bears N.29°E., 15 lks., with blaze healed. (Old BT)
A Hemlock 18" dia., bears S.55°W., 23 lks., with blaze healed. (Old BT)
A Fir 20" dia., bears S.59 3/4°E., 29 lks., mkd. 1/4 S22 BT. (New BT)

Doug. County Surveyors Office - Vernon Tracy; Jack Heritage Aug/Sept. 1966 - C.S. File 54/27-68

Found - GLO brass cap mkd. in 1943, with steel fence post alongside.

Both orig. BTs are down and out of place, scribe marks visible on SW BT.

1943 BT, gone completely.

New BTs - 5" D.Fir S.31°E., 16.2 ft. mkd. 1/4 S22 CS BT.
5" Cedar S.71 1/2°W., 31.1 ft. mkd. 1/4 S22 CS BT.
8" D.Fir N.47°W., 42.4 ft. mkd. 1/4 S15 CS BT.

Corner lies on SW slope, 2 ch. east of small creek, course N.15°W.