

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3700)

Set fir post, 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor., mkd. 1/4 S on N. face, from which

A chinquapin, 6" dia., bears N.45 1/2° W., 11 lks. dist., mkd. 1/4 S BT.

A Fir 20" dia., bears S.5° E., 26 lks. dist., mkd. 1/4 S BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11574)

The original 1/4 sec. cor., the locus of which has been perpetuated by a county surveyors fir stake, 3 ft. long, 4" sq. firmly set, mkd. 1/4 S3 CS on N., and 1/4 S10 on S. face. At point for corner, set an iron post, 3 ft. long, 1" dia., 28" in the ground, with the county surveyor's marked stake deposited at the base, for 1/4 sec. cor., with brass cap mkd.

1/4	-----
	S3
	S10

1944 from which

A fir, 40" dia., bears N.37° E., 33 lks. dist., mkd. on bark 1/4 S 3 BT CS. I re-blaze and re-mark this county surveyor's bearing tree 1/4 S3 BT.

A fir 24" dia., bears S.10° E., 26 lks. dist., with partial scribe marks on charred face of old blaze. I re-blaze and re-mark this old bearing tree 1/4 S10 BT.

Doug. County Surveyors Office - Vernon Tracy; Joe Brady; Jack Heritage - August 1966 - C.S. File 54/27-36

Found - GLO brass cap mkd. 1944.

40" now 40" fir stump, N.37° E., 21.8 ft., shows "1/4 S3 BT" on unhealed blaze. Norman Price calls this tree a CS BT.

Orig. 24" now 25" Fir stump, S.10° E., 17.2 ft., shows "1/4 S10 BT" on unhealed blaze.

New BTs - 5" D. Fir N.68° E., 17.6 ft. mkd. 1/4 S3 CS BT.

5" Hemlock S.30° E., 6.3 ft. mkd. 1/4 S10 CS BT.

This cor. lies on fairly steep, south slope in heavy brush and reproduction of fir, hemlock and cedar.