

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 460160

PRIMARY CORNER DESCRIPTION NE 1/6 Sec 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Wm Barnes - For: Weyerhaeuser Co. & Eugene Veneer Co. -  
May/June 1963 - C.S. File 51/261

-----  
Transit survey. Bearings based on assumed North Meridian from  
magnetic North using magnetic declination of 21°E  
Set 1" iron pipe for corner by double proportionate method.  
Referenced by W. Wilt (Weyerhaeuser Method with disc. #2128)  
26" R.Cedar S.89°W., 25.8'  
34" Fir N.30°W., 30.5'  
See also W. Wilt, Weyco, 6/1963 - C.S. File 53/113-15

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W.  
Saveland, Cadastral Surveyors and Robert H. Browning, Survey  
Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCS0  
records Vol. 57 Page(s) 22443-4)

-----  
Point for the NE 1/16 sec. cor. of sec. 34, at intersection  
with the E and W centerline of the NE ¼.  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with  
brass cap marked: NE 1/16 S34  
2008

from which  
A fir, 13" dia., bears N.38¾°E., 20.2 ft., mkd: X BT.  
A fir, 19" dia., bears S.26½°W., 29.4 ft., mkd: X BT.  
Deposit a magnet in a white plastic case at the base of the  
stainless steel post  
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at  
the base right side-center.  
From this cor., a point established by Barnes in 1963  
monumented by Wm Wilt, Land Agent in 1963, bears  
N.70°30'33"E., 16.11 ft., monumented with an iron pipe, 1¼"  
dia., firmly set, projecting 1" above ground, from which the  
remains of reference trees mkd. by Barnes  
A sawed, hollow cedar stump, 31" dia., bears N.88¾°W.,  
28.2 ft., with a brass washer mkd: REG. ENGR. NO. ORE.  
2128 and a metal tag.  
A sawed fir stump, 37" dia., bears N.27¾°W., 31.8 ft.,  
with axe marks and a brass washer mkd. REG. ENGR. NO.  
ORE. 2128 and a metal tag.  
This point was not correctly positioned and is not utilized  
in the course of this survey.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff  
Lorsung- 5/30/2023 - C.S. File 67/56-25

-----  
Found - 3¼" BLM brass cap up 3" (properly mkd)  
1" I.D. iron pipe N.70°30'33"E., 16.11 ft. 3" below  
ground (Corner set by Barnes C.S. 51/261) Cont.

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 460160

PRIMARY CORNER DESCRIPTION NE 1/6 Sec. 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Burned, low cut 17"x4" tall fir stump N.38¼°E., 20.2 ft. Face inside tree.  
Burned, dead, 16" fir S.19°E., 28.5 ft. (rec. S.26½°E., 29.4 ft.) fully healed single blaze, add 3½" mag nail, right side center.  
Rotted burned 35"x3 ft fir stump N.27¾°W., 31.8 ft., nail in face.  
New - Burned, sawn 16"x1 ft. D.Fir stump N.26°W., 3.3 ft., 3½" mag nail top center.  
Note - Area burned 9/2020  
Compass decl. 14½°E.  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 190559.762 E 242288.602