

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Cor Secs 34 & 35; 2 & 3 T26-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 9 Page 3664)

Set post cor. to secs. 2, 3, 34 and 35, from which
A Red Fir 20" dia., bears N.67°E., 35 lks. dist.
A Red Fir 20" dia., bears S.20°E., 6 lks. dist.
A Red Fir 18" dia., bears S.45°W., 10 lks. dist.
A Red Fir 15" dia., bears N.58°W., 20 lks. dist.

GLO Dependent Resurvey by Norman D. Price, Under Special
Instructions dated 4/5/1940 (DCSO rec Volume 27 Pg 11506)

Point for original cor. of secs. 2, 3, 34 and 35, determined
by reference to the record measurements from the original
NE and SW bearing trees. At point for corner, Set an iron
post 3 ft. long 2" dia., 28" in the ground, for cor. of
secs. 2, 3, 34 and 35, with brass cap mkd:

T25S R3W
S34|S35
S3|S2
T26S
1943

from which
A Fir stub, 22" dia., bears N.69°E., 35 lks. dist., with
partial scribe marks discernible on face of old
bark blaze. (Old BT)
A Fir 36" dia., bears S.45°W., 10 lks. dist., with faint
scribe marks discernible on face of old bark blaze.
I reblaze and remark this old bearing tree T26S R3W S3 BT
An Incense Cedar 10" dia., bears N.20½°E., 45 lks. dist.,
mkd. T25S R3W S35 BT. (New BT)
A W.Fir 22" dia., bears S.67°E., 41 lks. dist., mkd. T26S
R3W S2 BT. (New BT)
An Incense Cedar 12" dia., bears N.62½°W., 19 lks. dist.
mkd. T25S R3W S34 BT. (New BT)

Glen McChesney, Land Agent, Weyerhaeuser Co. March 10-11,
1965 C.S. File 53/115

Found - 1943 GLO brass cap set from original NE & SW BTs.
22" Fir stub N.69°E., 23.1 ft. faint bark scribe
visible.
36" Fir S.45°W., 6.6 ft. face healed over on 42" Fir
10" I.Cedar N.20½°E., 29.7 ft. scribing visible.
22" W.Fir stub 8 ft. high S.67°E., 27.1 ft. Face.
12" I.Cedar N.62½°W., 12.5 ft. scribing visible.
New BTs- 46" Fir N.1°E., 21.4 ft. "W" nail & plat added.
24" x 8 ft. W.Fir stub, S.67°E., 27.0 ft. "W" nail
and plate added. cont.....

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Cor Secs 34 & 35; 2 & 3 T26-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

42" Fir S.60°W., 5.7 ft. "W" nail & plate added.
14" I.Cedar N.59°W., 12.1 ft. "W" nail & plate added

H. Christensen, for U.S.R. Company, Apr. 1998 - M 128-59

Found - 1943 GLO 2½" Brass cap 0.9' above ground.
BT's - 46" D.Fir, N.1°E., 21.4 ft., healed face, stump.
5" D.Fir, N.56°E., 10.9 ft., healed face, (no rec.)
10" D.Fir, S.26°E., 41.9 ft., healed face, (no rec.)
43" D.Fir, S.45°W., 6.6 ft., healed face.
23" Cedar, N.62°W., 12.5 ft., healed face.
Note - Set steel fence post 1 ft. north.

BLM dependent resurvey by Bryan s. Seibold, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1777, surveyed Aug./Sept. 1995 - (DCS0 records Vol. 52 Page(s) 19887)

Beginning at the cor. of secs. 2, 3, 34 & 35, on the N. bdy. of the Tp., monumented with an iron post, 2" diam., firmly set, projecting 11" above ground, with brass cap mkd.

T25S	R3W
S 34	S 35
S 3	S 2
T26S	
1943	

from which the remains of the original bearing trees
A sawed fir stump, 26" diam., bears N.69°E., 35 lks., no marks visible.
A fir, 43" diam. bears S.45°W., 10 lks., w/healed blaze and the remains of bearing trees mkd. by Price
A cedar root crown, bears N.20½°E., 45 lks., with cedar trunk, 13" diam., alongside, with scribe marks T25S R3W S35 visible on open blaze.
A cedar, 23" diam. bears N.62½°W., 19 lks., w/healed blaze and new bearing trees
A fir, 4" diam., bears N.56½°E., 16½ lks., mkd. X BT.
A fir, 9" dia. bears S.26½°E. 63½ lks. mkd. T26S R3W S2 BT

Fd. OK by H.Christensen, Oct. 1999 - M133-77

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 11/7/2007 - C.S. File 67/24-45

Found ok, 4 live BTs

continued next page

PRIMARY CORNER DESCRIPTION Cor Secs 34 & 35; 2 & 3 T26-3

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W. Saveland, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCSO records Vol. 57 Page(s) 22417)

The cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

A sawed fir stump, 26" dia., bears N.69°E., 23.1 ft., with no marks visible on an opened blaze.

A fir, 46" dia., bears S.45°W., 6.6 ft., with a healed blaze.

and the remains of bearing trees mkd. by Price

A decayed cedar stump, size indeterminate, bears N.20½°E., 29.7 ft., alongside of which is a down, decayed cedar snag, 12" dia., with scribe marks W 3 and other fragmentary scribe marks visible on a partially healed blaze.

A cedar, 30" dia., bears N.62½°W., 12.5 ft., with a healed blaze.

and the remains of a bearing tree mkd. by McChesney, in 1965

A sawed, decayed fir stump, 47" dia., bears N.½°W., 23.1 ft., with no marks visible.

and bearing trees mkd. by Seibold

A fir, 10" dia., bears N.56½°E., 10.9 ft., with a healed double blaze.

A fir, 13" dia., bears S.26½°E., 41.9 ft., with a healed blaze.

Corner is located on a SE. slope.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 9/6/2023 - C.S. File 67/56-65

Found - 2½" BLM brass cap (properly mkd) up 14"

OBTs - Burned-dead 46" D.Fir S.45°W., 7.1 ft. (rec. 6.6 ft) healed blaze 3½" mag nail, right side center.

BT by Price -

Burnt-sawn 30"x3 ft. cedar stump N.62½°W., 12.5 ft., 3½" mag nail, right side center.

BT by McChesney -

Burned mostly rotted 47" Fir stump, N.0½°W., 23.1 ft

BTs by Seibold -

Burned-dead, 11" D.Fir N.57½°E., 10.7 ft. (rec. N.56½°E., 10.9 ft.) healed blaze 3½" mag nail, right side center.

Burned-dead, 15" D.Fir S.25½°E., 41.9 ft., 3½" mag nail, right side center. Continued next pg

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Cor Secs 34 & 35; 2 & 3 T26-3

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New - Metal post 1' NNW
Burned-dead 31" hemlock S.4°W., 25.8 ft., 3½" mag
nail, right side center.
Note: Tree not blazed or scribed.
Note - Area burnt 9/2020
Compass decl. 14½°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 186301.569 E 244626.371