

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 500160

PRIMARY CORNER DESCRIPTION N 1/16 Secs 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Wm Barnes - For: Weyerhaeuser Co. & Eugene Veneer Co. -  
May/June 1963 - C.S. File 51/261

-----  
Transit survey. Bearings based on assumed North Meridian from  
magnetic North using magnetic declination of 21°E  
Set 1" iron pipe for corner by single proportionate method.  
Referenced by W. Wilt (Weyerhaeuser Method with disc. #2128)  
10" R.Cedar N.36°E., 19.0'  
8" Fir N.29°W., 17.0'

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W.  
Saveland, Cadastral Surveyors and Robert H. Browning, Survey  
Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCS0  
records Vol. 57 Page(s) 22428-9)

-----  
The N 1/16 sec. cor. of secs. 34 & 35, established by Wm.  
Barnes in 1963, monumented by Wm. Wilt, Land Agent, in 1963,  
is accepted as the cor., monumented with an iron pipe, 1¼"  
dia., firmly set, projecting 16" above ground, with an  
electrician's star lock nut and a smashed, threaded top, from  
which reference trees mkd. by Barnes

A cedar, 13" dia., bears N.35½°E., 19.7 ft., with no marks  
visible, with a brass washer mkd: REG. ENGR. NO. ORE.  
2128 at base and a metal tag.

A fir, 20" dia., bears N.29½°W., 17.7 ft., with no marks  
visible and a metal tag.

At the corner point

Drive in iron pipe & set a stainless steel post directly over  
it, 28" long, 2½" dia., 24" in the ground, w/brass cap mkd:

N 1/16  
S34|S35  
2008

from which new BTs

A fir, 7" dia., bears N.53¼°E., 23.5 ft mkd: N 1/16 S35 BT

A fir, 10" dia., bears N.50°W., 17.0 ft mkd: N 1/16 S34 BT

Place iron pipe inside the stainless steel post and deposit  
a magnet in a white plastic case at the base of the stainless  
steel post.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff  
Lorsung- 5/30/2023 - C.S. File 67/56-26

-----  
Found - 3½" BLM brass cap (properly mkd) up 2"

Burned, sawn, 16"x1½ ft cedar stump N.35½°E., 19.8  
ft. (rec. 19.7 ft) with brass washer marked REG.  
ENGR. NO ORE 2128, add 3½" mag nail top center.

Continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 500160

PRIMARY CORNER DESCRIPTION N 1/16 Secs 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Burned, dead, 24" D.Fir N.29½°W., 17.1 ft., (rec. 17.7 ft.) add 3½" mag nail right side center.  
Burned, sawn, 9"x1/2" fir stump N.53¼°E., 23.5 ft. evidence of face inside.  
Burned, dead, 11" D.Fir N.50°W., 16.8 ft. (rec. 17.0 ft) fully healed single blaze add 3½" mag nail right side center.  
Note - BC mon. is N.45°W., 4.5 ft. from gravel road running N.35°E., and S.35°W.  
Archie Burnt 9/2020  
Compass decl. 14½°E.  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N. 190691.637 E. 244738.013