

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Pages 3680-81)

 Set Hemlock post 4 ft. long 4" sq., 24" in the ground for cor. to secs. 26, 27, 34 and 35, mkd. T25S S26 on NE., R3W S35 on SE., S34 on SW., and S27 on NW. faces, with 1 notch on S. and 2 notches on E. edges, from which

- A Dogwood, 6" dia., bears N.20°E., 36 lks. dist., mkd. T25S R3W S26 BT.
- A Hemlock 12" dia., bears S.70°E., 40 lks. dist., mkd. T25S R3W S35 BT.
- A Chinquapin 10" dia., bears S.62°W., 53 lks. dist., mkd. T25S R3W S34 BT.
- A Fir 30" dia., bears N.55°W., 45 lks. dist., mkd. T25S R3W S27 BT.

GL0 Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Pages 11553-54)

 Point for original cor. of secs. 26, 27, 34 and 35, determined by reference to the record measurements from all the original bearing trees. At point for corner, set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.

T25S R3W
S27 S26

S34 S35

1943 from which

- A Dogwood, 12" dia., bears N.19°E., 36 lks. dist., mkd. T25S R3W S26 BT. (Old BT)
- A Hemlock 12" dia., bears S.50½°E., 40 lks. dist., with blaze healed. (Old BT)
- A chinquapin 14" dia., bears S.61°W., 53 lks. dist., mkd. T25S R3W S34 BT.
- A dead Fir 30" dia., bears N.45°W., 45 lks. dist., mkd. on bark T25S R3W S27 BT. (Old BT)
- A sugar pine 10" dia., bears N.19½°E., 22 lks. dist., mkd. T25S R3W S26 BT. (New BT)
- A Fir 26" dia., bears S.15½°E., 62 lks. dist., mkd. T25S R3W S35 BT. (New BT)
- A sugar pine 72" dia., bears S.18°W., 67 lks. dist., mkd. T25S R3W S34 BT. (New BT)
- A Fir 48" dia., bears N.82¼°W., 58 lks. dist., mkd. T25S R3W S27 BT.

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Doug. County Surveyors Office - Vernon Tracy; Joe Brady; Jack Heritage - June/July 1966 - C.S. File 54/27-2

Found - 1943 GLO brass cap mkd.
Orig. 12" Dogwood N.19°E., 23.8 ft. shows
fragmentary scribe, alive.
Orig. 30" Fir, now snag N.45°W., 29.7 ft., not
opened.
10" now 15" S.Pine N.19½°E., 14.5 ft., alive, shows
good scar.
48" now 57" Fir N.82¾°W., 38.3 ft., alive, face
pitched over.
SE and SW BTs, now stumps.
New BTs - 10" Hemlock S.7½°W., 39.8 ft. mkd. T25S R3W S34 CSBT
14" Hemlock S.51°E., 37.8 ft. mkd. T25S R3W S35 CSBT
This cor. lies in NW corner of cut off unit.

Found OK, Nick Juliano, Dec. 1976, C.S. 58/130

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W. Saveland, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCSO records Vol. 57 Page(s) 22429-30)

The cor. of secs. 26, 27, 34, and 35, perpetuated by the Douglas County Surveyor's Office in 1966, monumented with an iron post, 2" dia., firmly set, projecting 11" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees
A decayed hemlock stump, size indeterminate, bears
S.50¾°E., 26.4 ft., with no marks visible.

A burned, decayed fir stump, 19" dia., bears N.45°W.,
29.7 ft., with no marks visible on an open blaze.

and the remains of bearing trees mkd. by Price

A decayed pine stump, size indeterminate, bears
N.19½°E., 14.5 ft., with no marks visible.

A sawed, decayed fir stump, 28" dia., bears S.15½°E.,
40.9 ft., with no marks visible.

A sawed, decayed, hollow pine stump, 72" dia., bears
S.18°W., 44.2 ft., with no marks visible.

A fir snag, 56" dia., bears N.82¾°W., 38.3 ft., with axe
marks visible on a healed blaze.

and a BT mkd. by the Douglas County Surveyor's Office

A hemlock, 17" dia., bears S.50¾°E., 37.6 ft., with
fragmentary scribe marks visible on a partially
healed double blaze.

continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing trees
A fir, 8" dia., bears N.45¾°E., 42.8 ft., mkd. T25S R3W S26 BT.
A fir, 4" dia., bears S.72¼°W., 32.3 ft., mkd. X at breast height and BT at base.
A fir, 12" dia., bears N.60¾°W., 7.4 ft., mkd. T25S R3W S27 BT.
Corner is located on a gradual, broken, SE. slope.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 12/4/2024 - C.S. File 67/59-22

Found - 1943 GLO brass cap (properly mkd), 11" above ground. Cap leans slightly east in rough mound of stone.
Decayed, burnt 18"x3½' Fir stump, S.15½°E., 40.9 ft. Blaze heal visible.
Burnt, bark-less 42"x30 ft. Fir snag, N.82¼°W., 39.0 ft. (rec, 38.3 ft.) Burnt blaze. Add 3½" mag nail left side center.
Burnt, dead 18" Hemlock S.50¾°E., 37.6 ft., fully healed double blaze, add 3½" mag nail, right side center.
Sawn, burnt 9"x1 ft. pistol butt Fir stump N.45¾°E., 42.6 ft. (rec. 42.8 ft.) partly healed blaze scribes visible, add 3½" mag nail top center.
Burnt, dead 13" Fir N.60¾°W., 7.4 ft., healed single blaze, add 3½" mag nail, right side center.
New - Burned, sawed, decayed pine stump S.18°W., 44.2 ft.
Burnt, dead 20" D.Fir N.21°E., 2.2 ft., add 3½" mag nail right side center. Very old illegible yellow tag.
Note - Area burnt 9/2020
Compass decl. 14¼°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 192024.706 E 244733.770