

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Pages 3684-85)

Set Cedar post 4 ft. long 4 sq., 24" in the ground for cor. to secs. 14, 15, 22 and 23, mkd. T25S S14 on NE., R3W S23 on SE., S22 on SW., and S15 on NW faces, with 3 notches on S. and 2 notches on E. edges, from which

- A Fir 16" dia., bears N.35°E., 41 lks. dist., mkd.
T25S R3W S14 BT.
- A Fir 20" dia., bears S.40°E., 30 lks. dist., mkd.
T25S R3W S23 BT.
- A Fir 25" dia., bears S.71°W., 14 lks. dist., mkd.
T25S R3W S22 BT.
- A Fir 18" dia., bears N.46°W., 34 lks. dist., mkd.
T25S R3W S15 BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Pages 11557-58)

Point for original cor. of secs. 14, 15, 22 and 23, determined at record distances from all old bearing trees. At point for corner, set an iron post, 3 ft. long, 2" dia., 28" in the ground, for corner, with brass cap mkd. T25S R3W

S15	S14
S22	S23

1943 from which

- A Fir 12" dia., bears N.35°E., 41 lks. dist., with partial scribe marks visible on face of partially healed old blaze. (Old BT)
- A Fir 20" dia., bears S.35°E., 30 lks. dist., with partial scribe marks visible on face of partially healed old blaze. (Old BT)
- A Fir 32" dia., bears S.64°W., 14 lks. dist., with old blaze healed. (Old BT)
- A dead Fir 12" dia., bears N.48°W., 34 lks. dist., mkd.
T25S R3W S15 BT. (Old BT)
- A Fir 20" dia., bears N.20°W., 46 lks. dist., mkd.
T25S R3W S15 BT. (New BT)

Doug. County Surveyors Office - Vernon Tracy; Joe Brady;
Jack Heritage - July/Aug. 1966 - C.S. File 54/27-54

(Cont. Next Page)

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 15 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Found - GLO brass cap mkd. 1943, & steel fence post alongside.
Orig. 12" now 16" Fir N.35°E., 27.1 ft., previously opened & shows "T25S RS, scribe. (now dead snag) (1883)
Orig. 20" now 27" R.Fir S.35°E., 19.8 ft. now stump shows scar. (1883)
Orig. 32" now 48" Fir S.64°W., 9.2 ft. alive, shows good scar. (1883)
Orig. NW BT, now gone and 1943 BT to NW, now turned out stump. (1883)
New BTs - 7" Hemlock N.36°E., 5.5 ft. mkd. T25S R3W S14 CS BT.
16" Hemlock N.70°W., 47.5 ft. mkd. T25S R3W S15 CSBT
8" Hemlock S.4°E., 21.7 ft. mkd. T25S R3W S23 CS BT.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 10/31/2022 - C.S. File 67/54-30

Found - 1943 2½" GLO brass cap on 1½" I.D. I.pipe, up 12" Burned-broken off rotted 19"x1½' R.Fir stump, S.37½°E., (rec. S.35°E.) 19.8 ft. 1883
Burned-broken off 31"x6½' fir stump S.62°W., (rec. S.64°W.) 10.5 ft. (rec. 9.2 ft) 1883
Singed sawn 30"x2½' hemlock stump N.36°E., 5.5 ft. blaze & partial scribe visible inside. 1966
Singed & sawn 27"x2½' hemlock stump S.4°W., 21.0 ft (rec 21.7 ft) evidence of face inside. 1966
All BTs have 3½" mag spikes - top center spiked if 4' or less, right side center spiked otherwise
Note - Area burnt 9/2020
Compass decl. 14½°E.
Corner is on moderate WNW slope approx 200 ft. south of gravel spur road.
O CRS Coordinates Cottage Grove - Canyonville Zone
N 204430.187
E 245530.935