

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10, 11

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3688)

Set Yew post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 2, 3, 10 and 11 mkd. T 25 S S 2 on NE., R3W S11 on SE., S10 on SW., and S3 on NW faces, with 5 notches on S. and 2 notches on E. edges, from which

A fir, 20" dia., bears N.55°E., 20 lks. dist., mkd. T25S R3W S2 BT.

A Chinquapin, 4" dia., bears S.64°E., 12 lks. dist., mkd. T25S R3W S11 BT.

A Fir 4" dia., bears S.61°W., 12 lks. dist., mkd. T25S R3W S10 BT.

A Fir 5" dia., bears N.15°W., 17 lks. dist., mkd. T25S R3W S3 BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11561)

Point for orig. cor. of secs. 2, 3, 10 and 11, determined at record measurements from old NE. and SW. bearing trees.

At point for corner, set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.

T25S R3W	
S3	S2

S10	S11
1943	

from which

A fir, 36" dia., bears N.55°E., 20 lks. dist., with partial scribe marks on old bark blaze. I reblaze and remark this old bearing tree T25S R3W S2 BT.

A fir, 48" dia., bears S.51°W., 12 lks. dist., with only ax marks on charred bark blaze. I reblaze and remark this old bearing tree T25S R3W S10 BT.

A fir 10" dia., bears S.40°E., 36 lks. dist., mkd. T25S R3W S11 BT. (New BT)

A fir 8" dia., bears N.38°W., 30 lks. dist., mkd. T25S R3W S3 BT. (New BT)

continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. 2, 3, 10, 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Doug. County Surveyors Office - Ray Tracy; Joe Brady; Jack Heritage - August, 1966 - C.S. File 54/27-35

Found - GLO brass cap mkd., 1943, with steel fence post set alongside.
Orig. 36" fir, now shattered blow-down, lying face down, N.55°E., 13.2 ft.
Orig. 48" now 50" burned fir stump, S.51°W., 7.9 ft. no scribe.
10" now 11" badly burned fir stump S.40°E., 23.8 ft. no scribe.
8" now 11" Fir, 6 ft. high snag, N.38°W., 19.8 ft. shows very good scar. To preserve, we do not open.
New BTs - 3" Chinquapin S.7½°W., 40.7 ft. mkd. S10 CS BT.
3" Laurel N.84°E., 18.5 ft. mkd. S2 CS BT.
(Only available BTs)
This corner lies on very steep NW slope of ridge, course west.