

PRIMARY CORNER DESCRIPTION 1/4 Corner for Secs. 23 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Pages 3683-84)

-----

Set Cedar post, 3 ft. long 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on N. face, from which

A Fir 8" dia., bears S.60°E., 23 lks. mkd. 1/4 S BT.

A Fir 6" dia., bears N.31°E., 43 lks. mkd. 1/4 S BT.

---

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11556)

-----

Proportional measurement. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S23}{S26}$$
 1943

from which

A Fir 24" dia., bears N.73°E., 85 lks., mkd. 1/4 S 23 BT.

A Fir 32" dia., bears S.29½°E., 54 lks., mkd. 1/4 S26 BT.

---

Doug. County Surveyors Office - Vernon Tracy; Joe Brady; Jack Heritage - June 1966 - C.S. File 54/27-11

-----

Found - 1943 GLO brass cap mkd.

24" now 26" Fir snag, N.73°E., 56.1 ft. Healed blaze, do not open. Snag approx. 60 ft. high.

32" now 36" Fir S.29½°E., 35.6 ft. Alive, shows good scar.

New BT - 8" Hemlock N.34°E., 7.2 ft. mkd. 1/4 S23 CS BT.

This cor. lies on southerly slope of spur approx. 150 ft. north of small creek, course SE.

---

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1701, Surveyed June/July 1993 - (DCSO records Vol. 51 Page(s) 19255-56)

-----

At the 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, with brass cap mkd.

$$1/4 \frac{S 23}{S 26}$$
 1943

from which the remains of bearing trees mkd. by Price

A fir snag, 26" dia., bears N.73°E., 85 lks. with scribe marks 1/4 S23 BT visible on an opened blaze.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A roothole, bears S.29½°E., 54 lks., with a down fir stump alongside, 36" dia., with a healed blaze.  
and new bearing trees  
A fir, 26" dia., bears N.7½°E., 66 lks. mkd. ¼ S23 BT.  
A fir, 4" dia., bears S.5¼°W., 20 lks. X at breast height and BT at the base.

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W. Saveland, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCSO records Vol. 57 Page(s) 22433)

-----  
The ¼ sec. cor. of secs. 23 & 26, determined at record bearing and dist. from the bearing trees mkd. by Bedell  
A fir, 25" dia., bears N.7½°E., 43.6 ft., with a healed blaze.  
A fir, 9" dia., bears S.5¼°W., 13.2 ft., with a healed blaze.  
At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, with brass cap mkd. T25S R3W  
¼  $\frac{S\ 23}{S\ 26}$   
2008  
(Note: The iron post, 36" long, 1" dia., with brass cap mkd. ¼ S23 S26 1943, set by Price, was found lying loose on the ground nearby.)  
Bury the iron post along the SE. side of the stainless steel post and bury a magnet in a white plastic case at the base of the stainless steel post.