

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3688)

-----  
Set Cedar post 3" sq., 3 ft. long, 24" in the ground for 1/4 sec. cor. mkd. S on W. face, from which  
A Fir 30" dia. bears N.10°E. 5 lks. dist. mkd. 1/4 S BT.  
A Hemlock 18" dia. bears N.19°W. 17 lks. dist. mkd. 1/4 S BT.

-----  
GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11560)

-----  
Proportional measurement. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor. with brass cap mkd.  $\frac{1}{4} \frac{S11}{S14}$  1943 from which  
A Fir 40" dia., bears N.25½°E., 70 lks. mkd. 1/4 S11 BT.  
An Incense Cedar 28" dia., bears S.89°W., 58 lks. mkd. 1/4 S14 BT.

-----  
Doug. County Surveyors Office - Vernon Tracy; Joe Brady; Jack Heritage - July/Aug. 1966 - C.S. File 54/27-55

-----  
Found - GLO brass cap mkd. 1943, and steel fence post alongside.  
28" now 32" Cedar stump S.89°W., 38.3 ft., shows scribe.  
NE BT, now burned & turned out stump, no scribe fd.  
New BTs - 6" D.Fir N.73°E., 5.5 ft. mkd. 1/4 S11 CS BT.  
7" D.Fir S.45°W., 12.9 ft. mkd. 1/4 S14 CS BT.  
To expose brass cap, we cut a 24" piece out of a log and straighten brass cap. Corner lies in old logging, now grown up to very thick D.Fir reproduction.

-----  
Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 12/10/2025 - C.S. File 67/61-51

-----  
Found - 2½" GLO brass cap leans 0± but solid in rocky soil. Appears undisturbed.  
Burnt out cedar stub S.88°W. 38.3 ft. to root center.  
15" x 7 ft. broke D. Fir snag N.73°E. 5.5 ft. No blaze visible. Add 3½" mag nail right side center.  
14" x 8 ft. sawn, burned D. Fir snag. S.45°W. 12.9 ft. fully healed single blaze. Add 3½" mag nail right side center.

Continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - 14" x 1½ ft. D. fir stump S.56°E. 13.0 ft. add 3½"  
mag nail top center.  
12" x 1½ ft. D. fir stump N.65°W. 22.5 ft. add 3½"  
mag nail top center.

Notes - Area burnt 9/2020  
Mon on M/L flat ground in very large clearcut.

Compass decl. 14¼°E.  
TRIMBLE GEO XT LOCATION.  
43.40525682 N.  
123.01966859 W.