

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3689)

-----  
Set Cedar post, 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on N. face, from which

A Fir 8" dia., bears N.13°W., 17 lks. dist., mkd. 1/4 S BT.

A Fir 6" dia., bears S.23°W., 42 lks. dist., mkd. 1/4 S BT.

-----  
GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11562)

-----  
Proportional measurement. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap mkd

1/4  $\frac{S2}{S11}$   
1944

from which

A Red Cedar 14" dia., bears N.80 1/2°E., 92 lks. dist., mkd. 1/4 S2 BT.

A Red Cedar 48" dia., bears S.80 1/2°W., 48 lks. dist., mkd. 1/4 S11 BT.

-----  
Not Fd - DCSO office, Vernon Tracy - 1966 - C.S. File 54/27-62