

PRIMARY CORNER DESCRIPTION Sec. Cor. 35 & 36; 1 & 2 of T.26-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #56 dated March, 1855  
(DCSO Records, Volume 9 Page 3664)

-----  
Set post cor. to secs. 1, 2, 35 and 36, from which  
A Cedar 12" dia., bears N.1°E., 22 lks. dist.  
A Red Fir 20" dia., bears N.39°W., 25 lks. dist.  
A Red Fir 28" dia., bears S.82°W., 33 lks. dist.  
A Maple 2" dia., bears S.62°E., 18 lks. dist.

GLO Dependent Resurvey by Norman D. Price, Under Special  
Instructions dated April 5, 1940 (DCSO records, Volume 27  
Page 11507)

-----  
Proportional measurement. Set an iron post, 3 ft. long 2"  
dia., 28" in the ground, for cor. of secs. 1, 2, 35 & 36,  
with brass cap marked:

|          |     |
|----------|-----|
| T25S R3W |     |
| S35      | S36 |
| -----    |     |
| S2       | S1  |
| T26S     |     |
| 1943     |     |

1943 from which  
A Fir 20" dia., bears N.30°E., 8 lks. dist., mkd. T25S  
R3W S36 Bt.  
A Fir 24" dia., bears S.72°E., 81. lks. dist. mkd. T26S  
R3W S1 BT.  
A Fir 20" dia., bears S.84°W., 50 lks. dist. mkd. T26S  
R3W S2 BT.  
A Fir 20" dia., bears N.57½°W., 40 lks. dist. mkd. T25S  
R3W S35 BT.

Fd. OK by H.Christensen, Apr. 1998 - M 128-59  
Fd. OK by H.Christensen, Oct. 1999 - M133-77

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike  
- 11/8/2007 - C.S. File 67/24-43

-----  
Found - 2½" dia., brass cap properly marked on 2" O.D. Iron  
pipe, projects 14" above ground in mound of  
stones.  
20" now 31" dia., x 1½ ft. tall D.Fir stump, tagged.  
No marks visible bears N.30°E., 6.0 ft. (Rec.  
N.30°E., 5.3 ft.) 1943 BT.  
24" now 40" dia., x 2½ ft. tall D.Fir stump, tagged,  
healed rotted blaze bears S.72°E., 53.5 ft.  
(agrees w/rec) 1943 BT  
20" now 29" dia., x 4 ft. tall D.Fir stump, tagged,  
burline visible on rotting stump bears S.84°W.,  
33.0 ft. (agrees w/rec) 1943 BT. cont.....

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. 35 & 36; 1 & 2 of T.26-3

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

|        |  |
|--------|--|
| New -  | 20" now 34" dia., D.Fir, healed blaze, bears N.57½°W., 26.4 ft. (agrees w/rec) 1943 BT   |
|        | 8" dia., hemlock double blazed & scribed "T26S R3W S1 CS BT" bears S.13°E., 40.7 ft.     |
|        | 6" dia., Chinquapin double blazed & scribed "T26S R3W S2 CS BT" bears S.24½°W., 18.0 ft. |
| Note - | Corner lays on nearly flat E-W bench.<br>Compass decl. 16¼°E.                            |