

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3668)

 Set Cedar post, 4 ft. long, 4" sq., 24" in the ground, for corner, mkd. T25S S25 on NE., R3W S36 on SE., S35 on SW., and S26 on NW. faces, with 1 notch on S. and E. edges, from which
 A W.Fir, 10" dia., bears N.44°E., 60 lks. dist., mkd. T25S R3W S25 BT.
 A R.Fir, 8" dia., bears S.81°E., 45 lks. dist., mkd. T25S R3W S36 BT.
 A Sugar Pine, 30" dia., bears N.50°W., 45 lks. dist., mkd. T25S R3W S26 BT.
 A Cedar 20" dia., bears S.83°W., 15 lks. dist., mkd. T25S R3W S35 BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Pages 11540-41)

 Proportional measurement. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. with brass cap mkd.

T25S R3W	
S26	S25

S35	S36

1943

from which

A Fir 28" dia., bears N.14¼°E., 66 lks., mkd. T25S R3W S25 BT.
 A Fir 16" dia., bears S.26 3/4°E., 55 lks., mkd. T25S R3W S36 BT.
 A Fir 22" dia., bears S.71 3/4°W., 41 lks., mkd. T25S R3W S35 BT.
 A Fir 6" dia., bears N.53½°W., 62 lks. mkd. T25S R3W., S26 BT.

WEYCO 6/1959 CS 53/113-5
 Found OK, Glenn Baughman, March 1977, M 63-60
 Fd. Ok by D.Edwards, 4/1998 - M128-61

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W. Saveland, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCSO records Vol. 57 Page(s) 22430-1)

 The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd.

continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of bearing trees mkd. by Price
A fir, 50" dia., bears N.14¼°E., 43.6 ft., with a healed blaze.
A sawed, decayed fir stump, 29" dia., bears S.26¼°E., 36.3 ft., with no marks visible.
A fir, 45" dia., bears S.71¼°W., 27.1 ft., with a healed blaze.
A sawed, decayed fir stump, 17" dia., bears N.53½°W., 40.9 ft., with a healed blaze.
and new bearing trees
A cedar, 16" dia., bears S.49¼°E., 62.0 ft., mkd. T25S R3W S36 BT.
A fir, 6" dia., bears N.45½°W., 62.6 ft., mkd. T25S R3W S26 BT.
Corner is located on a broken E. slope.