

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3672)

-----  
Set Dogwood post, on ridge course E. and W., 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on W. face, from which

A Fir 12" dia., bears N.20°E., 18 lks. dist., mkd. 1/4 S BT.

A Fir 36" dia., bears S.65°W., 25 lks. dist., mkd. 1/4 S BT.

GL0 Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Pages 11544-45)

-----  
Point for original 1/4 sec. cor. determined by reference to the record bearings from both old bearing trees. At point for corner, set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap mkd. 1/4

S23|S24  
1943

from which

A Fir 60" dia., bears N.20°E., 27 lks. dist., on which I uncovered the scribe marks 1/4 S BT beneath 60 years of overgrowth. I added the marks 24 to the inscription on this old bearing tree.

A Fir 36" dia., bears S.65°W., 74 lks. dist., on which I uncovered the scribe marks 1/4 S BT beneath 60 years of overgrowth. I added the marks 23 to the inscription on this old bearing tree.

The old blazed line passes directly through this cor. point.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jack Heritage - June 9, 1966 - C.S. File 54/7-62

-----  
Found - 1943 GL0 brass cap, out of ground.  
Orig. 36" now 42" Fir S.65°W., 48.8 ft., open, face pitched over, "23" scribe visible. Alive but top broken off approx. 80 feet up.

Orig. 60" now 70" Fir N.20°E., 17.8 ft., now stump & turned out, shows "24" scribe on face.

Reset - Brass cap mkd: "1/4 S 23|S24 1943"

New BTs - 14" Hemlock S.38°W., 70.9 ft. mkd. 1/4 S23 CS BT.

12" Hemlock N.58°E., 141.1 ft. mkd. 1/4 S24 CS BT

Corner falls on N. edge of cat road, course NE and SW and on edge of logged off unit in section 24

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1551, Surveyed Aug/ 1990/July 1991 - (DCSO records Vol. 51 Page(s) 19257-58)

-----  
The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. 1/4  
S 23 | S 24  
1943

from which the remains of the original bearing trees  
A roothole, bears N. 20° E., 27 lks. dist., with a down fir stump alongside, 60 ins. diam., with scribe marks 24 visible on a rotted blaze.  
A fir stump, 4 ft. high, with metal cap, 42 ins. diam., bears S. 65° W., 74 lks. dist., with scribe mark 2 visible on a partially opened blaze.  
and the remains of bearing trees mkd. by Vernon Ray Tracy, Deputy County Surveyor, in 1966  
A hemlock stump, 12 ins. diam., bears N. 58° E., 214 lks. dist., with scribe marks 1/4 S24 CS visible on a rotted blaze.  
A hemlock stump, 20 ins. diam., bears S.37°W., 107 lks., with illegible scribe marks on a rotted blaze.  
and new bearing trees  
A fir, 14 ins. diam., bears S. 50° E., 15 1/2 lks. dist., mkd. 1/4 S24 BT.  
A fir, 4 ins. diam., bears S. 82° W., 25 lks. dist., mkd. X at breast height and BT at the base.

From this point, the United States Coast and Geodetic triangulation station "SCOTT," bears S. 83° 09' 20" W. (mean bearing), 212.330 chs. dist. (sea level distance), monumented with a brass disk, 1" dia., mkd. X, inside a brass collar, 3" dia., mkd. USC & GS, cemented into solid rock.

Fd. BC, 2 1993 BTs & 1 OBT stump by D. Edwards - 12/2006 - M151-74

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W. Saveland, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCSO records Vol. 57 Page(s) 22423-4)

-----  
The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1" dia., firmly set, projecting 6 ins. above a collar of stone, with brass cap (properly) mkd.  
continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees  
A roothole bears N.20°E., 17.8 ft., alongside of which is an uprooted, sawed, decayed fir stump, 60" dia., with fragmentary scribe marks visible on a partially healed blaze.  
A sawed fir stump, 36" dia., bears S.65°W., 48.8 ft., with scribe marks 23 visible on a partially healed blaze, with a metal cover.  
and the remains of bearing trees mkd. by the Douglas County Surveyors Office in 1966, reported by Bedell  
A sawed, decayed fir stump, 15" dia., bears N.55°E., 141.2 ft., with fragmentary scribe marks visible on a partially healed blaze.  
A sawed hemlock stump, 18" dia., bears S.37°W., 70.6 ft., with fragmentary scribe marks visible on a partially healed blaze, with a metal cover.  
and bearing trees mkd. by Bedell  
A fir, 17" dia., bears S.50°E., 10.2 ft., with a healed blaze.  
A fir, 8" dia., bears S.82°W., 16.5 ft., with a healed blaze.  
and the remains of a bearing tree mkd. by person(s) unknown  
A sawed, decayed fir stump, 48" dia., bears N.31½°W., 55.2 ft., with a healed blaze and Weyerhaeuser aluminum bearing tree tag mkd. W.T. CO. Sec. 23 TWP 25 S. R. 8 W. 54.5 FT. S 31 E TO E ¼ COR.  
Corner is located on a gradual S. slope.

Fd. OK by DCSO: Stephen Flause & Jeff Lorsung 7-7-2020 - C.S. File 67/046-036 - Lat: 43.37689621 Long: -123.012550933

Douglas Co. Surveyors Office - Crew: Jeff Lorsung- 7/1/2024 - C.S. File 67/58-20

-----  
Found - GLO brass cap (properly mkd)  
A sawed, decayed Fir stump 15", N.55°E., 141.2 ft.  
A sawed hemlock stump, 18", S.37°W., 70.6 ft. partly healed blazes with metal cap.  
A 17" Fir S.50°E., 10.2 ft. with healed blaze.  
An 8" Fir S.82°W., 16.5 ft with healed blaze.  
Side spikes still there (2020 DCSO renewal)  
New tags, flagging.  
Note - Area burnt 9/2020  
Compass decl. 14¼°E.  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 198271.058 E 249334.116